

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS3007R-18T

Key features

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4/ v3 family
- Intel® C612 chipset
- Up to 1TB ECC 3DS LRDIMM , up to DDR4- 2400MHz ; 8x DIMM slots
- 1x PCI-E 3.0 x8 (FHHL) slot
- 8x 2.5" Hot-swap SAS3/SATA3 Drive Bays
- Intel® i210 Dual-Port 1GbE LAN, Intel® X540 Dual-Port 10GBase-T LAN
- SAS3 (12Gbps) via LSI 3108
- I/O ports: 1x VGA, 2x USB 3.0
- 600W High-Efficiency Power Supply Platinum Level Certified
- Optional 2x 2.5" NVMe Drives Support
- 2x SuperDOM (Disk on Module) ports
- IPMI 2.0 + KVM with Dedicated LAN



Processor/Cache		Front Panel	
Processor	Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4/ v3 family	LED Indicators	Power status LED,HDD activity LED, 2x Network activity LEDs,Universal Information (UID) LED
Buttons		Buttons	Power On/Off button,System Reset button, UID button
Chipset		Drive Bays	
Chipset	Intel® C612 chipset	HDD Bays	8x 2.5" Hot-swap SAS3/SATA3 Drive Bays
		Peripheral Drives	1x Slim DVD-ROM drive (optional)
System Memory		Power Supply	
Memory Capacity	8x 288-pin DDR4 DIMM slots, Up to 1TB ECC 3DS LRDIMM, 256 ECC RDIMM	600W High-Efficiency Power Supply Platinum Level Certified	
Expansion Slots		Cooling System	
	1x PCI-E 3.0 x8 (FHHL) slot	4x 4cm fans with optimal fan speed control	
Integrated On-Board		Form Factor	
SAS	SAS3 (12Gbps) via LSI 3108 RAID 0, 1, 5, 6, 10, 50, 60 support,2GB DDR3 Cache	Form Factor	1U Rackmount
SATA	SATA3 (6Gbps); RAID 0, 1, 5, 10	Width:	17.2" (437mm),
LAN	2x RJ45 10GBase-T LAN ports, 2x RJ45 Gigabit Ethernet LAN ports, 1x RJ45 Dedicated IPMI LAN port	Height:	1.7" (43mm),
		Depth:	19.98" (508mm)
Add-on Options		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	
Optical Drive	Optional		