Tyrone Camarero Specifications

Camarero DS3007R-216R

Key features

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family
- Intel® C612 Express chipset
- Up to 2TB ECC 3DS LRDIMM, up to DDR4- 2400 MHz; 16x DIMM slots
- 1x PCI-E 3.0 x16, 6x PCI-E 3.0 x8 slots
- 8x 2.5" SAS3 and 8x 2.5" SATA3 Hot-swap Drive Bays
- Integrated IPMI 2.0 with KVM and Dedicated LAN
- Intel® i350 Dual port GbE LAN
- I/O ports: 2x SuperDOM, 1x VGA, 2x COM, 2x USB 3.0, 4x USB 2.0
- 3x 8cm high-performance PWM fans
- 920W Redundant Power Supplies Platinum Level (94%)









P	ro	C	ess	or/	/Ca	C	h	е
---	----	---	-----	-----	-----	---	---	---

Dual socket R3 (LGA 2011) supports Intel® Processor

Xeon® processor E5-2600v4/v3 family

Chipset

Intel® C612 Express chipset Chipset

System Memory

Memory Capacity 16x 288-pin DDR4 DIMM slots,Up to 2TB

ECC 3DS LRDIMM, 512GBECC RDIMM

Expansion Slots

PCI-Express 1x PCI-E 3.0 x16, 6x PCI-E 3.0 x8

(Low-profile AOC)

Integrated On-Board

SATA SATA3 (6Gbps); RAID 0, 1, 5, 10

SAS LSI 3108 SAS3 (12Gbps) controller;

HW RAID 0, 1, 5, 6, 10, 50, 60

LAN 2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port

Add-on Options

Optical Drive Optional

Front Panel

LED Indicators Power LED, Hard drive activity LED,

2x Network activity LEDs, System Overheat

LED / Fan fail LED /UID LED

Buttons Power On/Off button, System Reset button

Drive Bays

HDD bays 8x 2.5" SAS3 and 8x 2.5" SATA3 Hot-swap

drive bays

Optional DVD-ROM drive supports 1x slim Peripheral Bays

or 1x 5.25" DVD drive

Power Supply

920W Redundant Power Supplies Platinum Level (94%)

Cooling System

3x 8cm heavy duty fans with optimal fan speed control

Form Factor

Form Factor 2U Rackmount

> Width: 17.2" (437 mm), Height: 3.5" (89mm), Depth: 24.8" (630mm)

Email: info@tyronesystems.com For more/current product information, visit www.tyronesystems.com