

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS3007R-216RT4

Key features

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4/ v3 family;
- Intel® C612 chipset
- Up to 3TB ECC 3DS LRDIMM , up to DDR4- 2400MHz ; 24x DIMM slots
- 2x PCI-E 3.0 x16, 3x PCI-E 3.0 x8, and 1x PCI-E 2.0 x4 (in x8) slot
- 8x 2.5" SAS3 and 8x 2.5" SATA3 Hot-swap Drive Bays
- Quad 10GBase-T ports w/ Intel X540
- I/O ports: 2x SuperDOM, 1x VGA, 2x COM, 2x USB 3.0 (rear), 4x USB 2.0 (2 rear, 2 front), 1x Type A
- 3x 8cm high-performance PWM fans
- 920W Redundant Power Supplies Platinum Level (94%)



Processor/Cache		Front Panel	
Processor	Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4/ v3 family;	LED Indicators	Power status LED, HDD activity LED, 2x Network activity LEDs, Universal Information (UID) LED
		Buttons	Power On/Off button. System Reset button
Chipset		Drive Bays	
Chipset	Intel® C612 chipset	HDD Bays	8x 2.5" and 8x 2.5" Hot-swap drive bays
System Memory		Power Supply	
Memory Capacity	24x 288-pin DDR4 DIMM slots Up to 3TB ECC 3DS LRDIMM, 768 ECC RDIMM		920W Redundant Power Supplies Platinum Level (94%)
Expansion Slots		Cooling System	
PCI-Express	2x PCI-E 3.0 x16, 3x PCI-E 3.0 x8, 1x PCI-E 2.0 x4 (in x8)		3x 8cm heavy duty fans with optimal fan speed control
Integrated On-Board		Form Factor	
SAS	LSI 3108 SAS3 (12Gbps) controller; HW RAID 0, 1, 5, 6, 10, 50, 60	Form Factor	2U Rackmount
SATA	SATA3 (6Gbps); RAID 0, 1, 5, 10	Width:	17.2" (437mm) ,
LAN	4x RJ45 10GBase-T ports, 1x RJ45 Dedicated IPMI LAN port	Height:	3.5" (89mm),
		Depth:	24.8" (630mm)
Add-on Options		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	
Optical Drive	None		