Tyrone Camarero Specifications

Tyrone

Camarero DS3007R-316RT

Key features

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/v3 family
- Intel® C612 chipset
- Up to 2TB ECC 3DS LRDIMM, up to DDR4- 2400MHz; 16x DIMM slots
- 1 PCI-E 3.0 x16, 6 PCI-E 3.0 x8 (slot 1 & 2 occupied by controller and JBOD expansion port)
- Dual 10GBase-T LAN w/ Intel® X540
- 16x 3.5" Hot-swap SAS3/SATA3 drive bays; 2x 2.5" optional Hot-swap drive bays (rear)
- SAS3 Hardware RAID controller and JBOD Expansion; RAID 0,1,5,6,10,50,60
- Server remote management: IPMI 2.0 / KVM over LAN / Media over LAN
- 2x 80mm hot-swap rear exhaust PWM fans
- 920W Redundant Power Supplies Platinum Level (94%)







Processor/Cache

Processor Dual socket R3 (LGA 2011) supports

Intel® Xeon® processor E5-2600v4/v3 family

Chipset

Chipset Intel® C612 chipset

System Memory

Memory Capacity 16x 288-pin DDR4 DIMM slots,

Up to 2TB ECC 3DS LRDIMM,

512 ECC RDIMM

Expansion Slots

PCI-Express 1 PCI-E 3.0 x16 slot,

6 PCI-E 3.0 x8 slots,

Slot 1 & 2 occupied by controller and JBOD Expansion Port

Integrated On-Board

SATA SATA3 (6Gbps) with RAID 0, 1, 5, 10
SAS SAS3 (12Gbps) via LSI 3108 AOC;

HW RAID. RAID 0, 1, 5, 6, 10, 50, 60

LAN 2x RJ45 10GBase-T LAN ports, 1x RJ45 Dedicated IPMI LAN port

Add-on Options

Optical Drive None

Front Panel

LED Indicators Power status LED, Hard drive activity LED,

2x Network activity LEDs,

System Overheat LED, Power fail LED

Buttons Power On/Off button, System Reset button

Drive Bays

HDD bays 16x 3.5" Hot-swap SAS3/SATA3 Drive Bays

Optional OS Drive 2x 2.5" optional rear Hot-swap 2.5" Drive

bays

Power Supply

920W Redundant Power Supplies Platinum Level (94%)

Cooling System

2x 80mm hot-swap rear exhaust cooling fans. Redundant cooling

Form Factor

Form Factor 3U Rackmount

 Height
 :
 5.2" (132mm),

 Width
 :
 17.2" (437mm),

 Depth
 :
 25.5" (648mm)

Email: info@tyronesystems.com

For more/current product information, visit www.tyronesystems.com