

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS3007T-212RT

Key features

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family
- Intel® C612 chipset
- Up to 2TB ECC 3DS LRDIMM , up to DDR4- 2400 MHz ; 16x DIMM slots
- 1x PCI-E 3.0 x16 Low-profile slot
- Intel® X540 Dual port 10GBase-T
- Integrated IPMI 2.0 with KVM and Dedicated LAN
- 3x 3.5" Hot-swap SAS/SATA HDD Bays
- LSI 3108 SAS3 controller (3 ports); RAID 0, 1, 5, 10
- 2000W Redundant Power Supplies Titanium Level (96%)



Processor/Cache		Front Panel	
Processor	Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family	LED Indicators	Power status LED HDD activity LED , 2x Network activity LEDs Universal Information (UID) LED
		Buttons	Power On/Off button UID button
Chipset		Drive Bays	
Chipset	Intel® C612 chipset	Hotswap	3x 3.5" Hot-swap SAS/SATA HDD trays
System Memory		Power Supply	
Memory Capacity	16x 288-pin DDR4 DIMM slots, Up to 2TB ECC 3DS LRDIMM, 512GB ECC RDIMM	2000W Redundant Power Supplies Titanium Level (96%)	
Expansion Slots		Cooling System	
PCI-Express	1x PCI-E 3.0 x16 Low-profile slot	4x 8cm heavy duty PWM fans with optimal fan speed control	
Integrated On-Board		Form Factor	
SAS	LSI 3108 SAS3 controller (3 ports); RAID 0, 1, 5, 10	Form Factor	2U Rackmountable
LAN	2x RJ45 10GBase-T ports 1x RJ45 Dedicated IPMI LAN port	Width	17.25" (438mm),
		Height	3.47" (88mm),
		Depth	30.5" (774mm)
Add-on Options		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	
Optical Drive	None		