Tyrone Camarero Specifications

Camarero DS3007TPG-224R

Key features

Two hot-plubbable systems (nodes)in a 2U form factor. Each node supports the following.

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/v3 family
- Intel® C612 chipset
- Up to 2TB ECC 3DS LRDIMM, up to DDR4-2400 MHz; 16x DIMM slots
- 1x PCI-E 3.0 x16, 1x PCI-E 3.0 x8 slot, and 1x PCI-E 3.0 x16 for GPU/Xeon Phi support (w/ GPU kit)
- Intel® i350-AM2 Dual port GbE LAN
- Integrated IPMI 2.0 with KVM and Dedicated LAN
- 12x 2.5" Hot-swap SAS (8) / SATA (4) HDD Bays
- LSI 3108 SAS3 controller (8 ports); RAID 0, 1, 5, 6, 10, 50, 60
- mSATA (full size) support
- 1280W Redundant Power Supplies Platinum Level Digital (94%)





Processor/Cache

Dual socket R3 (LGA 2011) supports Intel® Processor

Xeon® processor E5-2600v4/v3 family

Chipset

Intel® C612 chipset Chipset

System Memory

Memory Capacity 16x 288-pin DDR4 DIMM slots, Up to 2TB

ECC 3DS LRDIMM, 512 ECC RDIMM

Expansion Slots

PCI-Express 1x PCI-E 3.0 x16 Low-profile slot, 1x PCI-E

3.0 x8 slot, 1x PCI-E 3.0 x16 for GPU/Xeon

Phi support (w/ GPU kit)

Integrated On-Board

SAS LSI 3008 SAS3 (12Gbps) controller; RAID

0, 1, 5, 6, 10, 50, 60 support. Optional

SuperCap

LAN 2x RJ45 Gigabit Ethernet LAN ports,

1x RJ45 Dedicated IPMI LAN port

Add-on Options

Optical Drive None

Front Panel

LED Indicators Power status LED, HDD activity LED,

2x Network activity LEDs, Universal

Information (UID) LED

Buttons 7SS Power On/Off button, UID button

Drive Bays

HDD bays 12x 2.5" Hot-swap SAS (8) / SATA (4)

HDD Bays

Power Supply

1280W Redundant Power Supplies Platinum Level Digital (94%)

Cooling System

4x 8cm heavy duty PWM fans with optimal fan speed control

Form Factor

Form Factor 2U Rackmount

Width: 17.25"(438mm), Height: 3.47" (88mm), 28.75" (730mm) Depth:

Email: info@tyronesystems.com For more/current product information, visit www.tyronesystems.com