

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS300TG-424RT

Key features

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family
- Intel® C612 Express chipset
- Up to 3TB ECC 3DS LRDIMM , up to DDR4- 2400 MHz ; 24x DIMM slots
- 8 PCI-E 3.0 x16 (double-width) slots. 2 PCI-E 3.0 x8 (in x16) slots 1 PCI-E 2.0 x4 (in x16) slot
- Intel® i350 Dual port GbE LAN Or Intel® X540 Dual port 10G Base-T LAN
- 24x 2.5" Hot-swap drive bays
- I/O Ports: 2xLAN, 1xDedicated LAN for IPMI Remote Management, 1xVGA, 4xUSB 3.0
- 8x 92mm RPM Hot-Swap cooling fans
- 4U Rackmountable, 1600W Redundant (2+2) Power Supplies; Platinum Level (94%+)



Processor/Cache		Drive Bays	
Processor	Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family	HDD bays	24x 2.5" Hard drive bays
Chipset		Power Supply	
Chipset	Intel® C612 Express chipset	1600W Redundant (2+2) Power Supplies; Platinum Level (94%+)	
System Memory		Cooling System	
Memory Capacity	24x 288-pin DDR4 DIMM slots, Up to 3TB ECC 3DS LRDIMM, 768GB ECC RDIMM	8x 92mm RPM Hot-Swappable Cooling Fans	
Expansion Slots		Form Factor	
PCI-Express	8x PCI-E 3.0 x16 (double-width) slots 2x PCI-E 3.0 x8 (in x16) slots 1x PCI-E 2.0 x4 (in x16) slot	Form Factor	4U Rackmountable
Integrated On-Board		Width:	17.2" (437mm),
SATA	SATA3 (6Gbps) with RAID 0, 1, 5, 10	Height:	7.0" (178mm),
LAN	2x RJ45 Gigabit/10Gigabit Ethernet LAN ports, 1x RJ45 Dedicated IPMI LAN port	Depth:	29" (737mm)
Add-on Options		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	
Raid	Optional		