# **Tyrone Camarero Specifications**

# Tyrone

# Camarero DS300TG8-424R

#### **Key features**

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4/v3 family
- Intel® C612 chipset
- Up to 3TB ECC 3DS LRDIMM, up to DDR4- 2400MHz; 24x DIMM slots
- 8x PCI-E 3.0 x16 (double-width) slots 2x PCI-E 3.0 x8 (in x16) slots 1x PCI-E 2.0 x4 (in x16) slot
- Dual 10GBase-T LAN with Intel® X540
- 24x 2.5" Hot-swap drive bays
- 8x 92mm RPM Hot-Swap cooling fans
- 1600W Redundant (2+2) Power Supplies; Platinum Level (94%+)





	ce				

Dual socket R3 (LGA 2011) supports Processor

Intel® Xeon® processor E5-2600 v4/ v3 family

#### Chipset

Intel® C612 chipset Chipset

# **System Memory**

**Memory Capacity** 24x 288-pin DDR4 DIMM slots,

Up to 3TB ECC 3DS LRDIMM,

1.5TB ECC RDIMM

#### **Expansion Slots**

**PCI-Express** 8x PCI-E 3.0 x16 (double-width) slots

> 2x PCI-E 3.0 x8 (in x16) slots 1x PCI-E 2.0 x4 (in x16) slot

# Integrated On-Board

SATA SATA3 (6Gbps); RAID 0, 1, 5, 10

LAN 2x RJ45 10GBase-T LAN ports,

1x RJ45 Dedicated IPMI LAN port

# **Add-on Options**

**Optical Drive** None Front Panel

**LED Indicators** Power LED, Hard drive activity LED,

> 2x Network activity LEDs, System Overheat LED, Power Fail LED

**Buttons** Power On/Off button, System Reset button

**Drive Bays** 

HDD Bay 24x 2.5" Hard drive bays

# **Power Supply**

1600W Redundant (2+2) Power Supplies; Platinum Level (94%+)

#### Cooling System

8x 92mm RPM Hot-Swappable Cooling Fans, 1x Air Shroud (MCP-310-84806-0B), 1x Air Shroud (MCP-310-84807-0B)

#### Form Factor

Form Factor 4U Rackmountable, Rackmount

Kit (MCP-290-00057-0N)

Width: 17.2" (437mm), Height: 7.0" (178mm), Depth: 29" (737mm)

Email: info@tyronesystems.com For more/current product information, visit www.tyronesystems.com