

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS300TR-11R

Key features

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family
- Intel® C612 Express chipset
- Up to 1TB ECC 3DS LRDIMM, up to DDR4- 2400 MHz ; 8x DIMM slots
- 1x PCI-E 3.0 x8 (FHHL) slot
- 2x 2.5" Fixed SATA3 Drive Bays
- Intel® i350 Dual-Port 1GbE LAN
- I/O ports: 1x VGA, 1x COM, 4x USB 2.0
- 400W Redundant Power Supplies Gold Level Certified
- 2x SuperDOM (Disk on Module) ports
- IPMI 2.0 + KVM with Dedicated LAN



Processor/Cache		Front Panel	
Processor	Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family	LED Indicators	Power status LED,HDD activity LED, 2x Network activity LEDs, Universal Information (UID) LED
		Buttons	Power On/Off button,System Reset button
Chipset		Drive Bays	
Chipset	Intel® C612 Express chipset	HDD Bays	2x 2.5" Fixed SATA3 Drive Bays
System Memory		Power Supply	
Memory Capacity	8x 288-pin DDR4 DIMM slots, Up to 1TB ECC 3DS LRDIMM, 512 ECC RDIMM	400W Redundant Power Supplies Gold Level Certified	
Expansion Slots		Cooling System	
PCI-Express	1x PCI-E 3.0 x8 (FHHL) slot	5x 4cm fans with optimal fan speed control	
Integrated On-Board		Form Factor	
SATA	SATA3 (6Gbps); RAID 0, 1	Form Factor	1U Rackmount
LAN	2x RJ45 Gigabit Ethernet LAN ports, 1x RJ45 Dedicated IPMI LAN port	Width:	17.2" (437 mm),
		Height:	1.7" (43mm),
		Depth:	16.9" (429mm)
Add-on Options		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	
Raid	Optional		
Optical Drive	None		

© Intel, the Intel logo,the Intel Inside logo,Xeon,and Intel Xeon Phi are trademarks of intel Corporation in the U.S and/Or other Countries
 © Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks .All other brands and names are the property of their respective owners