

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS300TR-45R

Key features

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4/ v3 family
- Intel® C612 chipset
- Up to 2TB ECC 3DS LRDIMM , up to DDR4- 2400 MHz ; 16x DIMM slots
- 10x PCI-E 3.0 x8 (FHFL) slots, 1x PCI-E 2.0 x4 (in x8) slot
- Intel® i350 Dual port Gigabit Ethernet
- 5x 3.5" Hot-swap HDD Bays
- 3x 5.25" Peripheral Drive Bays
- 600W Redundant Power Supplies Platinum Level (94%)



Processor/Cache		Front Panel	
Processor	Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4/ v3 family	LED Indicators	Power LED, Hard drive activity LED, 2x Network activity LEDs, System information (overheat/UID) LED, Power Fail LED
Chipset	Intel® C612 chipset	Buttons	Power On/Off button, System Reset button
System Memory		Drive Bays	
Memory Capacity	16x 288-pin DDR4 DIMM slots , Up to 2TB ECC 3DS LRDIMM, 512 ECC RDIMM	HDD Bays	5x 3.5" Hot-swap Drive Trays , 3x 5.25" Peripheral Drive Trays
Expansion Slots		Peripheral	1x slim DVD-ROM drive (optional)
PCI-Express	10x PCI-E 3.0 x8 slots, 1x PCI-E 2.0 x4 (in x8) slot	Power Supply	
Integrated On-Board		600W Redundant Power Supplies Platinum Level (94%)	
SATA	SATA3 (6Gbps) with RAID 0, 1, 5, 10	Cooling System	
LAN	2x RJ45 Gigabit Ethernet LAN ports, 1x RJ45 Dedicated IPMI LAN port	1x 92x38mm 4-pin PWM front intake fan , 2x 80x38mm 4-pin PWM rear exhaust fans	
Add-on Options		Form Factor	
Raid	Optional	Form Factor	4U Rackmountable / Tower
Optical Drive	Optional	Width:	7.0" (178mm) ,
		Height:	17.2" (437mm),
		Depth:	20.68" (525mm)
		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	