

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS300TT-212RI

Key features

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family
- Up to 1TB ECC 3DS LRDIMM , up to DDR4- 2400MHz ; 8x DIMM slots
- 1x PCI-E 3.0 (x16) low-profile slot
- Single port IB (FDR, 56Gbps), w/ QSFP connector
- Intel® i350 Dual port GbE LAN
- 3x 3.5" Hot-swap SATA3 drive bays
- 2x SATA DOM
- 1600W Redundant Power Supplies Titanium Level



Processor/Cache		Front Panel	
Processor	Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family	LED Indicators	Power status LED HDD activity LED 2x Network activity LEDs Universal Information (UID) LED
Buttons		Buttons	Power On/Off button System Reset button UID button
Chipset		Drive Bays	
Chipset	Intel® C612 chipset	HDD bays	3x 3.5" Hot-swap SATA3 HDD trays
System Memory		Power Supply	
Memory Capacity	8x 288-pin DDR4 DIMM slots, Up to 1TB ECC 3DS LRDIMM, 256GB ECC RDIMM	1600W Redundant Power Supplies Titanium Level	
Expansion Slots		Cooling System	
PCI-Express	1x PCI-E 3.0 (x16) Low-profile slot 1x PCI-E 3.0 (x8) connectors for SMCI Add-on Cards	4x 8cm heavy duty PWM fans with optimal fan speed control	
Integrated On-Board		Form Factor	
SATA	SATA3 (6Gbps) with RAID 0, 1, 5	Form Factor	2U Rackmount
LAN	2x RJ45 Gigabit Ethernet LAN ports, 1x RJ45 Dedicated IPMI LAN port	Width	17.25" (438mm),
		Height	3.47" (88mm),
		Depth	28.5" (724mm)
Add-on Options		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	
Raid	Optional		
Optical Drive	None		

○ Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S and/or other Countries
 ○ Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks .All other brands and names are the property of their respective owners