

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS300TTR-212R

Key features

Two hot-pluggable systems (nodes) in a 2U form factor. Each node supports the following.

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/v3 family
- Intel® C612 chipset
- Up to 1TB ECC 3DS LRDIMM , up to DDR4- 2400 MHz ; 8x DIMM slots
- 3x PCI-E 3.0 x8 slots (1x low-profile and 2x FHHL)
- Intel® i350 Dual port GbE LAN
- 6x 3.5" Hot-swap SATA3 drive bays
- 2x SATA DOM
- 1280W Redundant Power Supplies Platinum Level



Processor/Cache	
Processor	Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/v3 family
Chipset	
Chipset	Intel® C612 chipset
System Memory	
Memory Capacity	8x 288-pin DDR4 DIMM slots, Up to 1TB ECC 3DS LRDIMM, 256 ECC RDIMM
Expansion Slots	
PCI-Express	1x PCI-E 3.0 (x8) Low-profile slot, 2x PCI-E 3.0 (x8) Full-height Half-length slots
Integrated On-Board	
SATA	SATA3 (6Gbps) with RAID 0, 1, 5, 10
LAN	2x RJ45 Gigabit Ethernet LAN ports, 1x RJ45 Dedicated IPMI LAN port
Add-on Options	
Raid	Optional
Optical Drive	None

Front Panel	
LED Indicators	Power status LED, HDD activity LED, 2x Network activity LEDs, Universal Information (UID) LED
Buttons	Power On/Off button, UID button
Drive Bays	
HDD bays	6x 3.5" Hot-swap SATA3 HDD trays
Power Supply	
1280W Redundant Power Supplies Platinum Level	
Cooling System	
4x 8cm heavy duty PWM fans with optimal fan speed control	
Form Factor	
Form Factor	2U Rackmount
Width:	17.25" (438mm),
Height:	3.47" (88mm),
Depth:	28.5" (724mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	