

# Tyrone Camarero Specifications

**Tyrone**<sup>®</sup>

## Camarero DS300TTR-224R

### Key features

**Four hot-pluggable systems (nodes) in a 2U form factor. Each node supports the following:**

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/v3 family
- Intel® C612 chipset
- Up to 1TB ECC 3DS LRDIMM, up to DDR4- 2400MHz ; 8x DIMM slots
- 1x PCI-E 3.0 x16 (LP) slot
- Intel® i350 Dual port GbE LAN
- 6x 2.5" Hot-swap SATA3 drive bays
- 1600W Redundant Power Supplies Titanium Level
- 2x SATA DOM



Processor/Cache		Front Panel	
Processor	Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/v3 family	LED Indicators	Power status LED, HDD activity LED, 2x Network activity LEDs, Universal Information (UID) LED
Chipset	Intel® C612 chipset	Buttons	Power On/Off button, System Reset button, UID button
System Memory		Drive Bays	
Memory Capacity	8x 288-pin DDR4 DIMM slots, Up to 1TB ECC 3DS LRDIMM, 256 ECC RDIMM	HDD bays	6x 2.5" Hot-swap SATA3 drive bays
Expansion Slots		Power Supply	
	1x PCI-E 3.0 (x16) Low-profile slot		1600W Redundant Power Supplies Titanium Level
Integrated On-Board		Cooling System	
SATA	SATA3 (6Gbps) with RAID 0, 1, 5, 10		4x 8cm heavy duty fans with PWM fan speed control
LAN	2x RJ45 Gigabit Ethernet LAN ports, 1x RJ45 Dedicated IPMI LAN port	Form Factor	
Add-on Options		Form Factor	2U Rackmount
Raid	Optional	Width:	17.25" (438mm),
Optical Drive	None	Height:	3.47" (88mm),
		Depth:	28.5" (724mm)
		<p><b>Email : <a href="mailto:info@tyronesystems.com">info@tyronesystems.com</a></b></p> <p><b>For more/current product information, visit</b></p> <p><b><a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b></p>	