

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS300TW-12R

Key features

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family
- Intel® C612 chipset
- Up to 2TB ECC 3DS LRDIMM , up to DDR4- 2400 MHz ; 16x DIMM slots
- 2x PCI-E 3.0 x16 (FHHL) slots
- 2x 2.5" Fixed drive bays w/ bracket
- Intel® i350 Dual port GbE LAN
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- I/O ports: 2x SuperDOM, 1x VGA, 1x COM, 2x USB 3.0, 4x USB 2.0
- 400W Redundant Power Supplies Gold Level; BBP option



Processor/Cache		Front Panel	
Processor	Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family	LED Indicators	Power LED Hard drive activity LED , 2x Network activity LEDs System Overheat LED
		Buttons	Power On/Off button System Reset button
Chipset		Drive Bays	
Chipset	Intel® C612 chipset	Internal	2x 2.5" Fixed drive bays with bracket
System Memory		Power Supply	
Memory Capacity	16x 288-pin DDR4 DIMM slots, Up to 2TB ECC 3DS LRDIMM, 512GB ECC RDIMM		400W Redundant Power Supplies Gold Level; BBP option
Expansion Slots		Cooling System	
PCI-Express	2x PCI-E 3.0 x16 Full-height, Half-length slots		4x 40x56mm PWM fan; 2x fans for AOC cooling
Integrated On-Board		Form Factor	
SATA	SATA3 (6Gbps); RAID 0, 1, 5, 10	Form Factor	1U Rackmountable
LAN	2x RJ45 Gigabit Ethernet LAN ports, 1x RJ45 Dedicated IPMI LAN port	Width	17.2" (437mm)
		Height	1.7" (43mm)
		Depth	16.9" (429mm)
Add-on Options		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	
Raid	Optional		
Optical Drive	None		

© Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S and/or other Countries
 © Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks .All other brands and names are the property of their respective owners