

# Tyrone Camarero Specifications

**Tyrone**<sup>®</sup>

## Camarero DS300TW-18

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family
- Up to 2TB ECC 3DS LRDIMM , up to DDR4- 2400 MHz ; 16x DIMM slots
- 2x PCI-E 3.0 x8 Full-height Half-length, 1x PCI-E 3.0 Low-profile
- 8x 2.5" Hot-swap SATA HDD bays
- Intel® i350 Dual port Gigabit Ethernet
- I/O ports: 2x SuperDOM, 1x VGA, 1x COM, 2x USB 3.0, 2x USB 2.0
- 600W High-efficiency Digital-switching Power Supply; Platinum Level



Processor/Cache	
Processor	Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family
Chipset	
Chipset	Intel® C612 Express chipset
System Memory	
Memory Capacity	16x 288-pin DDR4 DIMM slots, Up to 2TB ECC 3DS LRDIMM, 512GB ECC RDIMM
Expansion Slots	
PCI-Express	2x PCI-E 3.0 x8 full-height, Half-length slots 1x PCI-E 3.0 Low-profile slot
Integrated On-Board	
SATA	SATA3 (6Gbps); RAID 0, 1, 5, 10
LAN	2x RJ45 Gigabit Ethernet ports 1x RJ45 Dedicated IPMI LAN port
Add-on Options	
Raid	Optional
Optical Drive	Optional

Front Panel	
LED Indicators	Power status LED HDD activity LED 2x Network activity LEDs Universal Information (UID) LED
Buttons	Power On/Off button UID button
Drive Bays	
HDD bays	8x 2.5" Hot-swap SATA HDD trays
Peripheral Drives	1x Slim DVD-ROM drive (optional)
Power Supply	
600W High-efficiency Digital-switching Power Supply; Platinum Level	
Cooling System	
5x 4cm fans with optimal fan speed control	
Form Factor	
Form Factor	1U Rackmountable
	Width 17.2" (437mm) , Height 1.7" (43mm) , Depth 23.5" (597mm)
<p><b>Email : <a href="mailto:info@tyronesystems.com">info@tyronesystems.com</a></b></p> <p><b>For more/current product information, visit</b></p> <p><b><a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b></p>	