

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS300TX-38R

Key features

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/v3 family
- Intel® C612 chipset
- Up to 2TB ECC 3DS LRDIMM , up to DDR4- 2400 MHz ; 16x DIMM slots
- 10x PCI-E 3.0 x8 (FHFL) slots, 1x PCI-E 2.0 x4 (in x8) slot
- Intel® i350 Dual port Gigabit Ethernet
- 8x 3.5" Hot-swap drive bays, 2x 5.25" drive bays
- Server remote management: IPMI 2.0 / KVM over LAN / Media over LAN
- 3x middle fans & 1x rear exhaust fan
- 980W Redundant Power Supplies Platinum Level (94%)



Processor/Cache		Front Panel	
Processor	Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/v3 family	LED Indicators	Power status LED, Hard drive activity LED, 2x Network activity LEDs, System information (overheat/UID) LED, Power fail LED
Chipset	Intel® C612 chipset	Buttons	Power On/Off Button, System Reset Button
System Memory		Drive Bays	
Memory Capacity	16x 288-pin DDR4 DIMM slots, Up to 2TB ECC 3DS LRDIMM, 512 ECC RDIMM	HDD bays	8x 3.5" Hot-swap drive bays, 2x 5.25" drive bays
Expansion Slots	10x PCI-E 3.0 x8 slots, 1x PCI-E 2.0 x4 (in x8) slot	Peripheral Bays	1x slim DVD-ROM drive (optional)
Integrated On-Board		Power Supply	
SATA	SATA3 (6Gbps) with RAID 0, 1, 5, 10	980W Redundant Power Supplies Platinum Level (94%)	
LAN	2x RJ45 Gigabit Ethernet LAN ports, 1x RJ45 Dedicated IPMI LAN port	Cooling System	
Add-on Options		3x 8cm 7K RPM, Middle fans, 1x 8cm 6.7K RPM, Rear Exhaust fan	
Raid	Optional	Form Factor	
Optical Drive	Optional	Form Factor	3U Rackmount
		Height	: 5.2" (132mm),
		Width	: 17.2" (437mm),
		Depth	: 25.5" (648mm)
		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	