

Tyrone Camarero Specifications

Camarero DS4007E2-212R

Tyrone[®]

Key features

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4+/ v3 family; UPI up to 9.6GT/s
- Intel® C612 chipset
- Up to 2TB+ ECC 3DS LRDIMM , up to DDR4- 2400+MHz; 16 DIMM slots
- 1 PCI-E 3.0 x16, 6 PCI-E 3.0 x8 slots
- Intel® i350 Dual port GbE LAN
- 10 SATA3 (6Gbps) ports w/ Intel® C612 controller; RAID 0, 1, 5, 10
- 8 SAS3 (12Gbps) ports w/ Broadcom® 3108 controller (2GB cache);RAID 0, 1, 5, 6, 10, 50, 60
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- 5 USB 3.0 and 4 USB 2.0 ports
- 12 x 3.5" hot-swap SAS/SATA drive bay with SES3
- 3 x 8cm high-performance PWM fan(s)
- 920W Redundant Platinum Super Quiet power supply W/PMbus



Processor/Cache

Processor Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4+/ v3 family; UPI up to 9.6GT/s

Chipset

Chipset Intel® C612 chipset

System Memory

Memory Capacity Up to 2TB+ ECC 3DS LRDIMM , up to DDR4- 2400+MHz; 16 DIMM slots

Expansion Slots

PCI-Express 1 PCI-E 3.0 x16, 6 PCI-E 3.0 x8 slots

Integrated On-Board

SATA SATA3 (6Gbps); RAID 0, 1, 5, 10

SAS Broadcom 3108 SAS3 (12Gbps) controller; 2GB cache; HW RAID 0, 1, 5, 6, 10, 50, 60, Supports up to 16 devices as default, more HDD devices support is also available as an option

LAN 2 RJ45 Gigabit Ethernet LAN portS, 1 RJ45 Gigabit Ethernet LAN ports

Add-on Options

Optical Drive None

Front Panel

LED 2 Network Activity LEDs, Fan Fail/System Over Heat LED, HDD activity LED, Power Status LED, Unit Identification (UID) LED

Buttons Power On/Off button, System Reset button

Drive Bays

HDD Bays 12 x 3.5" hot-swap SAS/SATA drive bay with SES3

Power Supply

920W Redundant Platinum Super Quiet power supply W/PMbus

Cooling System

3 x 8cm high-performance PWM fan(s)

Form Factor

Form Factor : 2U Rackmount

Height : 3.5" (89 mm)
Width : 17.2" (437 mm)
Depth : 25.5" (647 mm)

Email : info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com