Tyrone Camarero Specifications

Camarero DS400GQ-12RT

Key features

- Up to 4 NVIDIA® Tesla® P100 SXM2 GPUs,Up to 80 GB/s GPU-to-GPU NVIDIA® NVLINK™,Optimized for NVIDIA® GPUDirect™ RDMA
- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 2 UPI up to 10.4 GT/s
- Intel® C621 chipset
- 12 DIMM slots, Up to 3TB 3DS ECC DDR4-2933MHz RDIMM/LRDIMM, Supports Intel® Optane™ DCPMM
- 4 PCI-E 3.0 x16 slots
- 2 Hot-swap 2.5" SAS/SATA, drive bays, 2 Internal 2.5" drive bays
- 2x 10GBase-T LAN ports via Intel X540
- Support 1x M.2 2242/2260/2280, Support M.2 SATA and NVMe
- 7 Heavy duty 4cm counter-rotating, fans with air shroud & optimal fan speed control
- 2000W Redundant Power Supplies, Titanium Level (96%)







Dro	000	COL			30
PIII	1.45				ш
Pro		301/	u	•	

Processor 2nd Generation Intel® Xeon® Scalable

Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 2 UPI up to 10.4 GT/s

Chipset

Chipset Intel® C621 Chipset

System Memory

Memory Capacity 12 DIMM slots, Up to 3TB 3DS ECC

DDR4-2933MHz RDIMM/LRDIMM, Supports Intel® Optane™ DCPMM

Expansion Slots

PCI-Express 4 PCI-E 3.0 x16 slots

Integrated On-Board

SATA 4 SATA3 (6Gbps) with RAID 0, 1, 5, 10

LAN 2 RJ45 10GBase-T ports,1 RJ45 Dedicated

IPMI LAN port

Add-on Options

Raid Card Optional

Optical Drive None

Front Panel

LED Indicators Power LED, Hard drive activity LED, Network

activity LEDs, System Overheat LED / Fan fail

LED /UID LED

Buttons Power On/Off button UID button

Drive Bays

HDD Bays 2 Hot-swap 2.5" SAS/SATA drive bays,

2 Internal 2.5" drive bays

M.2 Support 1x M.2 2242/2260/2280, Support

M.2 SATA and NVMe

Power Supply

2000W Redundant Power Supplies Titanium Level (96%)

Cooling System

7 Heavy duty 4cm counter-rotating fans with air shroud & optimal fan speed control

Form Factor

Form Factor 1U Rackmount

Height : 1.7" (43mm), Width : 17.2" (437mm), Depth : 35.2" (894m),

39.3" (997mm) with rails

Email: info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com

Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of intel Corporation in the U.S and/Or other Countries

Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners