

Tyrone Camarero Specifications

Tyrone

Camarero DS400TE1-224R

Key features

- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors, Dual Socket P (LGA 3647) supported, CPU TDP support 205W TDP, 3 UPI up to 10.4 GT/s
- Intel® C621
- Up to 4TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz, in 16 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only);
- 3 PCI-E 3.0 x16, 4 PCI-E 3.0 x8, M.2 Interface: 2 PCI-E 3.0 x4, M.2 Form Factor: 2242/2260/2280/22110, M.2 Key: M-Key (RAID 0,1 support)
- 1 VGA port
- Intel® C621 controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Dual LAN with 1GbE with Intel® X722 + Marvell 88E1512
- 24 x 2.5" hot-swap SAS/SATA drive bay, optional 2 x 2.5" hot-swap drive bay
- 3 x 8cm high-performance PWM fan(s) Optional 5 x 6cm 4pin high performance fan(s)
- 920/1000/1200W Redundant Power Supply



Processor/Cache

Processor	2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors, Dual Socket P (LGA 3647) supported, CPU TDP support 205W TDP, 3 UPI up to 10.4 GT/s
-----------	--

Chipset

Chipset	Intel® C621
---------	-------------

System Memory

Memory Capacity	Up to 4TB 3DS ECC RDIMM, DDR4-2933 MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz, in 16 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only);
-----------------	---

Expansion Slots

PCI-Express	3 PCI-E 3.0 x16, 4 PCI-E 3.0 x8, M.2 Interface: 2 PCI-E 3.0 x4, M.2 Form Factor: 2242/2260/2280/22110, M.2 Key: M-Key (RAID 0,1 support)
-------------	--

Integrated On-Board

SATA	Intel® C621 controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
SATA	2 1GbE LAN ports

Add-on Options

Raid Card	Optional
Optical Drive	None

Front Panel

LEDs	2 Network Activity LEDs, Fan Fail/System Over Heat LED, HDD activity LED, Power Status LED, Unit Identification (UID) LED
Buttons	Power On/Off button, System Reset button

Drive Bays

Drive bays	24 x 2.5" hot-swap SAS/SATA drive bay, optional 2 x 2.5" hot-swap drive bay
------------	---

Power Supply

Power Supply	920/1000/1200W Redundant Power supply
--------------	---------------------------------------

Cooling System

Cooling System	3 x 8cm high-performance PWM fan(s), Optional 5 x 6cm 4pin high performance fan(s)
----------------	--

Form Factor

Form Factor	2U Rackmount
Height	3.5" (89 mm)
Width	17.2" (437 mm)
Depth	24.8" (630 mm)

Email : info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com