

Tyrone Camarero Specifications

Tyrone®

Camarero DS400TG-12RT

Key features

- Supports up to 4 GPUs in 1U, Support Active/Passive GPUs, GPU health monitoring with Fan speed control
- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors. Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 3 UPI up to 10.4 GT/s
- Intel® C621 chipset
- Up to 3TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 3TB 3DS ECC LRDIMM, DDR4-2933MHz, in 12 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only)
- 4 PCI-E 3.0 x16 (FHFL) slots, 2 PCI-E 3.0 x16 (LP) slots
- 2 Hot-swap 2.5" SAS/SATA drive bays, 2 Internal 2.5" drive bays
- 2x 10GBase-T LAN ports via Intel X540
- 9 Heavy duty 4cm counter-rotating fans with air shroud & optimal fan speed control
- 2000W Redundant Power Supplies Titanium Level (96%)



Processor/Cache	
Processor	2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors. Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 3 UPI up to 10.4 GT/s
Chipset	
Chipset	Intel® C621 chipset
System Memory	
Memory Capacity	Up to 3TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 3TB 3DS ECC LRDIMM, DDR4-2933MHz, in 12 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only)
Expansion Slots	
PCI-Express	4 PCI-E 3.0 x16 (FHFL) slots, 2 PCI-E 3.0 x16 (LP) slots
Integrated On-Board	
SATA	4 SATA3 (6Gbps) with RAID 0, 1, 5, 10
LAN	2 RJ45 10GBase-T ports, 1 RJ45 Dedicated IPMI LAN port
Add-on Options	
Raid Card	Optional
Optical Drive	None

Front Panel	
LED Indicators	Power LED, Hard drive activity LED, Network activity LEDs, System Overheat LED / Fan fail LED / UID LED
Buttons	Power On/Off button, System Reset button
Drive Bays	
HDD Bays	2 Hot-swap 2.5" U.2 NVMe drive bays, Fixed :2 Internal 2.5" SATA drive bays M.2 :Support 1x M.2 2242/2260/2280, Support M.2 SATA and NVMe
Power Supply	
2000W Redundant Power Supplies Titanium Level (96%)	
Cooling System	
9 Heavy duty 4cm counter-rotating fans with air shroud & optimal fan speed control	
Form Factor	
Form Factor	1U Rackmount
Height	: 1.7" (43mm),
Width	: 17.2" (437mm),
Depth	: 35.2" (894mm), 39.3" (997mm) with rails
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	