Tyrone Camarero Specifications

Tyrone

Camarero DS400TN-28R

Key features

- Cloud and Virtualization needs, Compute Intensive Application, Database Processing and Storage, High Availability Storage, Hosting & Application Delivery
- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors. Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 2 UPI up to 10.4 GT/s
- Intel ®C621 chipset
- Up to 4TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz, in 16 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only);
- 4 PCI-E 3.0 x16, 2 PCI-E 3.0 x8 slots
- 8 Hot-swap 3.5° SATA3 drive bays; RAID 0, 1, 5, 10
- Optional DVD-ROM drive, optional support: 2 fixed 2.5" NVMe/SSD/HDD,1 M.2 support
- 2x 1GbE LAN ports with Intel® X722
- 740/800/1000W Redundant Power Supply





Processor/Cache

Processor 2nd Generation Intel® Xeon® Scalable

Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors.Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 2 UPI up to 10.4 GT/s

Chipset

Chipset Intel *C621 chipset

System Memory

Memory Capacity Up to 4TB 3DS ECC RDIMM, DDR4-2933

MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz, in 16 DIMM slots;Up to 2TB intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only);

Expansion Slots

PCI-Express 4 PCI-E 3.0 x16, 2 PCI-E 3.0 x8 slots

Integrated On-Board

SATA SATA3 (6Gbps); RAID 0, 1, 5, 10

IAN 2 RJ45 Gigabit Ethernet LAN ports,

1 RJ45 Dedicated IPMI LAN port

Add-on Options

Raid Card Optional Optical Drive None

Front Panel

LED Indicators Power status LED, HDD activity LED,

Network activity LEDs,

System information (overheat/UID) LED

Buttons Power On/Off button,

System Reset button, UID button

Drive Bays

HDD Bays 8 Hot-swap 3.5" SATA drive bays

Power Supply

740/800/1200W Redundant Power Supply

Cooling System

3 Heavy duty 80mm fans with PWM fan speed control

Form Factor

Form Factor 2U Rackmount

Height : 3.5° (89mm), Width : 17.2° (437mm), Depth : 25.5° (647mm)

Email: info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com