

# Tyrone Camarero Specifications



## Camarero DS400TTB-26R

### Key features

Compute Intensive Application, HPC, Data Center, Enterprise, Server, Hyperscale / Hyperconverged  
Four hot-pluggable systems (nodes) in a 2U form factor. Each node supports the following:

- Dual Socket P (LGA 3647), 2nd Gen. Intel® Xeon® Scalable Processors (Cascade Lake/Skylake), Dual UPI up to 10.4GT/s Support CPU TDP 70-205W, Up to 28 Cores  
Note 1: 200W/205W CPUs are supported under certain configurations. Please contact Tyrone Technical Support for additional information about specialized system optimization  
Note 2: BIOS version 3.0a or above is required to support 2nd Gen. Intel® Xeon® Scalable processors
- Intel® C621 chipset
- 24 DIMM slots, Up to 6TB 3DS ECC DDR4-2933MHz+ RDIMM/LRDIMM, Supports Intel® Optane™ DCPMM 2933/2666/2400/2133MHz ECC DDR4 RDIMM/LRDIMM  
Note : 2933MHz in two DIMMs per channel can be achieved by using memory purchased from Tyrone, Cascade Lake only. Contact your Tyrone sales rep for more info.
- 2 PCI-E 3.0 (x16) Low-profile slots 1 S10M card support (must bundle with network card)
- 6 Hot-swap 2.5" SATA3 drive bays
- IPMI 2.0 + KVM with dedicated LAN
- Video via Aspeed AST2500 BMC
- 4 Heavy duty 8cm PWM fans with air shroud
- 2200W Redundant Power Supplies Titanium Level (96%)



Processor/Cache	
Processor	Dual Socket P (LGA 3647), 2nd Gen. Intel® Xeon® Scalable Processors (Cascade Lake/Skylake), Dual UPI up to 10.4GT/s Support CPU TDP 70-205W, Up to 28 Cores Note 1: 200W/205W CPUs are supported under certain configurations. Please contact Tyrone Technical Support for additional information about specialized system optimization Note 2: BIOS version 3.0a or above is required to support 2nd Gen. Intel® Xeon® Scalable processors
Chipset	
Chipset	Intel® C621 chipset
System Memory	
Memory Capacity	24 DIMM slots, Up to 6TB 3DS ECC DDR4-2933MHz+ RDIMM/LRDIMM, Supports Intel® Optane™ DCPMM 2933/2666/2400/2133MHz ECC DDR4 RDIMM/LRDIMM Note : 2933MHz in two DIMMs per channel can be achieved by using memory purchased from Tyrone Cascade Lake only. Contact your Tyrone sales rep for more info.
Expansion Slots	
PCI-Express	2 PCI-E 3.0 (x16) Low-profile slots 1 S10M card support (must bundle with network card)
Integrated Onboard	
SATA	Intel® C621 controller for SATA3 (6 Gbps) ports; RAID 0,1,5,10
LAN	1 RJ45 Dedicated IPMI LAN port
Add-on Options	
Raid Card:	Optional
Optical Drive:	None

Front Panel	
LED's	Power status LED, HDD activity LED, Network activity LEDs, Universal Information (UID) LED
Buttons	Power On/Off button, UID button
Drive Bays	
HDD Bays	6 Hot-swap 2.5" SATA3 drive bays
Power Supply	
	2200W Redundant Power Supplies, Titanium Level (96%)
Cooling System	
	4 Heavy duty 8cm PWM fans with air shroud
Form Factor	
Form Factor	2U Rackmount
Dimensions	Width 17.6" (447mm), Height 3.47" (88mm), Depth 28.75" (730mm)
<p><b>Email : <a href="mailto:info@tyronesystems.com">info@tyronesystems.com</a></b>  <b>For more/current product information, visit</b>  <b><a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b></p>	

Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S. and/or other countries.  
Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners.