

Tyrone Camarero Specifications



Camarero DS400TW-18RL

Key features

Web Server, Firewall Apps. Corporate-Wins, DNS, Print, Login. Gateway, provisioning servers.

Compact Network Appliance. Cloud Computing

- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors. Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 2 UPI up to 10.4 GT/s
- Intel® C621 chipset
- Up to 3TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 3TB 3DS ECC LRDIMM, DDR4-2933MHz, in 12 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only)
- 2 PCI-E 3.0 x16 (FHHL) slots, 1 PCI-E 3.0 x8 (LP) slot, 1 PCI-E 3.0 x16 for Add-on-Module, 1 PCI-E M.2 SSD slot
- 8 Hot-swap 2.5" SAS/SATA drive bays
- Optional 1 slim DVD-ROM drive bay
- 2 1GbE LAN ports via Intel® X722
- 1 VGA, 4 USB 3.0 (rear)
- 2 SuperDOM (Disk on Module) ports
- 750W Redundant Power Supplies Platinum Level High-efficiency



| Processor/Cache | |
|---|--|
| Processor | 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors. Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 2 UPI up to 10.4 GT/s |
| Chipset | |
| Chipset | Intel® C621 chipset |
| System Memory | |
| Memory Capacity | Up to 3TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 3TB 3DS ECC LRDIMM, DDR4-2933MHz, in 12 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only) |
| Expansion Slots | |
| PCI-Express | 2 PCI-E 3.0 x16 (FHHL) slots, 1 PCI-E 3.0 x8 (LP) slot, 1 PCI-E 3.0 x16 for Add-on-Module, 1 PCI-E M.2 SSD slot |
| Integrated On-Board | |
| SATA | SATA3 (6Gbps); RAID 0, 1, 5, 10 |
| LAN | 2 RJ45 Gigabit Ethernet ports, 1 RJ45 Dedicated IPMI LAN port |
| Add-on Options | |
| Raid Card | Optional |
| Optical Drive | Optional |
| Front Panel | |
| LED Indicators | Power status LED, HDD activity LED, Network activity LEDs, Universal Information (UID) LED |
| Buttons | Power On/Off button, UID button |
| Drive Bays | |
| HDD Bays | 8 Hot-swap 2.5" SAS/SATA drive bays |
| Peripheral Bays | 1 Slim DVD-ROM drive bay (optional) |
| Power Supply | |
| 750W Redundant Power Supplies Platinum Level High-efficiency | |
| Cooling System | |
| 4 Counter-rotating 4cm PWM fans, 2 fans for cooling AOC | |
| Form Factor | |
| Form Factor | 1U Rackmount |
| Height | : 1.7" (43mm), |
| Width | : 17.2" (437mm), |
| Depth | : 23.5" (597mm) |
| <p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p> | |

© Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S and/or other countries
 © Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners