

Tyrone Camarero Specifications

Tyrone

Camarero DS4A0TR-54T

Key features

- EATX Server Board with dual Xeon Scalable processors
- Intel C622
- DDR4 2666 MHz RDIMM up to 768 GB (24 DIMMs)
- 5 PCIe x16 (Gen3) and one PCIe x8 (Gen3) for three double-deck cards
- Intel® X557-AT2 dual 10GbE ports
- 10 SATA3 and six USB3.0 ports
- One M.2 2280 (SATA / PCIe compatible)
- 0 ~ 40 °C ambient operation temperature range
- External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x5
- Front: 120 x 25 mm x1 PWM Fan,Rear: 120 x 25 mm x1 PWM Fan
- 500W Single PS, 80Plus,1200W Single PS, 80Plus Platinum



Processor/Cache

Processor EATX Server Board with dual Xeon Scalable processors

Chipset

Chipset Intel C622

System Memory

Memory Capacity DDR4 2666 MHz RDIMM up to 768 GB (24 DIMMs)

Expansion Slots

PCI-Express 5 PCIe x16 (Gen3) and one PCIe x8 (Gen3) for three double-deck cards

Integrated On-Board

SATA 10 x SATAIII (RAID 0,1,5,10)10 x SATAIII (RAID 0,1,5,10)

LAN LAN1: Intel I210AT; LAN2: Intel I210AT; LAN3/4: Intel X557-AT2, 10G Base-T

Add-on Options

Raid Card Optional

Optical Drive None

Front Panel

Led's Power status, HDD, LANs, System Fail Activity LEDs, ID

Buttons Power Switch, System Reset, USB 3.0 x 2

Drive Bays

HDD Bays External: 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x5

Power Supply

500W Single PS, 80Plus,1200W Single PS, 80Plus Platinum

Cooling System

120 x 25 mm PWM Easy-Swap Fan middle fan, Max 2 supported

Form Factor

Form Factor : 5U/Tower Rackmount

Height : 16.9"(430 mm)

Width : 7.9" (200 mm)

Depth : 22" (560mm)

Email : info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com