

Tyrone Camarero Specifications



Camarero DSA700TN-224RT

Key features

- Dual AMD EPYC™ 7001/7002* series Processors (*Board revision 2.x required), Socket SP3, Up to 240W TDP, Up to 32 Cores, Up to 64 Cores (Board revision 2.x required)
- System on Chip
- 16 DIMM sockets, Supports up to 2TB Registered ECC DDR4 2666MHz SDRAM in 16 DIMMs, Supports up to 4TB Registered ECC DDR4 3200MHz SDRAM (Board revision 2.x required), 8-channel memory bus
- Expansion slots : 2 PCI-E 3.0 x16;3 PCI-E 3.0 x8;M.2 Interface: 1 SATA/PCI-E 3.0 x2;M.2 Form Factor: 2280, 22110;M.2 Key: M-key
- 10 SATA3, 1 M.2, 2 SATA DOM
- Dual 10GBase-T LAN Ports
- ASPEED AST2500 BMC graphics
- Up to 2 USB 3.0 ports;Up to 4 USB 2.0 ports
- 8 4-pin PWM Fan & Speed control
- 24-port 2U SAS3 12Gbps single-expander backplane, support up to 20x 2.5-inch SAS3/SATA3 HDD/SSD and 4x NVMe/SAS3/SATA3 storage devices
- 24 x 2.5" hot-swap SAS/SATA drive bay, optional 2 x 2.5" hot-swap drive bay
- 3 x 8cm high-performance PWM fan(s), Optional 5 x 6cm 4pin high performance fan(s)
- 1200W/1000W Titanium Power Supply W/PMbus W76xL336xH40mm



Processor/Cache		Front Panel	
Processor	Dual AMD EPYC™ 7001/7002* series Processors (*Board revision 2.x required), Socket SP3, Up to 240W TDP, Up to 32 Cores, Up to 64 Cores (Board revision 2.x required)	Front Panel	2 Network Activity LEDs, Fan Fail/System Over Heat LED, HDD activity LED, Power Status LED, Unit Identification (UID) LED
		Buttons	Power On/Off button System Reset Button
Chipset		Drive Bays	
Chipset	System on Chip	HDD Bays	24 x 2.5" hot-swap SAS/SATA drive bay, optional 2 x 2.5" hot-swap drive bay
System Memory		Power Supply	
Memory Capacity	16 DIMM sockets, Supports up to 2TB Registered ECC DDR4 2666MHz SDRAM in 16 DIMMs, Supports up to 4TB Registered ECC DDR4 3200MHz SDRAM (Board revision 2.x required), 8-channel memory bus	1200W/1000W Titanium Power Supply W/PMbus W76xL336xH40mm	
Expansion Slots		Cooling System	
PCI-Express	2 PCI-E 3.0 x16;3 PCI-E 3.0 x8;M.2 Interface: 1 SATA/PCI-E 3.0 x2;M.2 Form Factor: 2280, 22110;M.2 Key: M-key	3 x 8cm high-performance PWM fan(s), Optional 5 x 6cm 4pin high performance fan(s)	
Integrated Onboard		Form Factor	
SATA	SATA3 (6 Gbps)	Form Factor	2U Rackmount
LAN	2 RJ45 10GBase-T ports;1 RJ45 Dedicated IPMI LAN port	Dimensions:	Height : 3.5" (89 mm); Width : 17.2" (437 mm); Depth : 24.8" (630 mm)
Add-on Options		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	
Raid Card:	Optional		
Optical Drive:	None		