

Tyrone Camarero Specifications



Camarero DT200T6G-46R

Key features

- Dual socket R (LGA 2011) supports Intel Xeon Processor E5-2600/E5-2600 v2 series processors
- up to 192GB UDIMM / 384GB RDIMM / 768GB LRDIMM
- Intel C602 Chipset
- (8) PCI-E Gen3 x16 slots / (2) PCI-E Gen3 x8 slots(one for mezzanine card) / (3) PCI-E Gen2 x1 s (1) PCI 32-bit slot
- IPMI 2.0 compliant baseboard management controller (BMC) / Supports storage over IP and remote platform-flash / USB 2.0 virtual hub
- (2) GbE ports (1 port shared with IPMI)
- 6 x 2.5" HDDs or 4 x 3.5" HDDs
- (5+1) hot-swap 12cm fans
- 2400W Redundant Power Supplies



Processor/Cache	
Processor	Dual socket R (LGA 2011) supports Intel Xeon Processor E5-2600/E5-2600 v2 series processors
Chipset	
	Intel C602 Chipset
System Memory	
Memory Capacity	(12)+(12) DIMM slots supports up to 192GB UDIMM / 384GB RDIMM / 768GB LRDIMM
Expansion Slots	
PCI-Express	(8) PCI-E Gen3 x16 slots / (2) PCI-E Gen3 x8 slots(one for mezzanine card) / (3) PCI-E Gen2 x1 slots, (1) PCI 32-bit slot
Integrated On-Board	
SATA	(1) Mini-SAS (4-ports) + (2) SATA (totally support 6 ports)
RAID	RAID 0/1/10/5 (Intel RST)
LAN	(2) GbE ports (1 port shared with IPMI), Intel I350-BT2 controller
Add-on Options	
Optical Drive	Optional

Front Panel :	
LED Indicators	Fan fail LED indicator / Over temperature warning indicator / Fan & PSU fail LED indicator
Buttons	(1) RST / (1) ID / (1) PWR w/ LED
Drive bays	
HDD bays	6 x 2.5" HDDs or 4 x 3.5" HDDs
Power Supply	
	2400W Redundant Power Supplies
Cooling System	
	(5+1) hot-swap 12cm fans
Form Factor	
	4U Rackmount Width- 30.31" (770 mm), Height- 17.24" (438 mm) , Depth – 6.93" (176 mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	