

Tyrone Camarero Specifications



Camarero DTA410TOG-28RT

Key features

- 2U 4-GPU HPC Server
- Dual-Socket AMD EPYC™ 7002 upto 200W
- 16 x DIMM slots
- PCIe Gen 4.0 support
- 8 x 3.5" SATA/NVMe U.2 tool-less drive bays
- Hot-swap redundant PSU



Processor/Cache	
Processor	2 x AMD Socket SP3, AMD EPYC™ 7002 Series Processors, Max up to 200W
Chipset	
Chipset	System on Chip
System Memory	
Memory Capacity	DDR4 ECC RDIMM/RDIMM 3DS/LRDIMM/ LRDIMM 3DS 3200, Up to 2,048GB RDIMM / 4,096GB LRDIMM 3DS, 8 Channels per CPU, 1.2V
Expansion Slots	
PCI-Express	4 x FH/FL PCI-E Gen4 x16 slots, 4 x FH/ FL PCI-E Gen4 x8 slots, 2 x HH/HL PCI-E Gen4 x16 slots
Integrated On-Board	
2 x 10GbE ports, 1 x GbE port dedicated for IPMI , 2 x SATA-DOM / 8 x SATA Ports, 6Gb/s, 4 x SFF-8654 for 8 x NVMe ports, 1 x D-Sub 15-pin graphics port, Up to 1920x1200 resolution, 2 x USB3.1 Gen1, 2 x USB3.1 Gen1 (Optional), 1 x USB3.1 Gen1 (Type-A), 1 x COM port (Optional)	
Add-on Options	
RAID	Optional SAS RAID Controllers, Hardware / Software
RAID Cache protection	Optional (for Hardware RAID Only)
TPM	Optional
Optical Drive	None

Drive Bays	
8 x 3.5/2.5" Hot-swap SSD/HDDs SAS 12Gb/s /SATA 6Gb/s /NVMe Backplane Support	
Power Supply	
2200 Watts, 1+1 Redundant Power Supplies, 80 plus Platinum Certified	
Cooling System	
5 x 8cm fans	
Form Factor	
Form Factor	2U Rackmount
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit www.tyronesystems.com</p>	