

Tyrone Camarero Specifications

Tyrone[®]

Camarero FDS200T36T-42R

Key features

Four Systems (Nodes) in 4U Form Factor. Each node supports:

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 1TB ECC DDR3, up to 1866MHz; 16x DIMM sockets
- Expansion slots: 1 PCI-E 3.0 x16 (LP), 1 PCI-E 3.0 x8 (LP) and 1 PCI-E 2.0 x4 (LP)
- Front I/O ports: 2 GbE LAN, 2 USB 2.0 and 1 VGA connector
- Built-in Server management tool(IPMI 2.0, KVM/media over LAN) with dedicated LAN port
- 2x 3.5" Hot-swap SATA HDDs
- 1280W Redundant Power Supplies Platinum Level (95%)



Processor/Cache	
Processor	Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
Chipset	
	Intel® C602 Chipset
System Memory	
	16x 240-pin DDR3 DIMM sockets Up to 1TB DDR3 ECC LRDIMM Up to 512GB DDR3 ECC Registered memory (RDIMM)
Expansion Slots	
PCI-Express	1 PCI-E 3.0 x16 (LP), 1 PCI-E 3.0 x8 (LP), 1 PCI-E 2.0 x4 (LP)
Integrated On-Board	
SATA	SATA 2.0 3Gbps with RAID 0, 1, 5, 10, SATA 3.0 6Gbps with RAID 0, 1
LAN	2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port
Add-on Options	
RAID Card	Optional
Optical Drive	None

Front Panel	
Buttons	Power On/Off button, System Reset button
LEDs	Power status LED, Hard drive activity LED, 2x Network activity LEDs, System Overheat LED, Power fail LED
Drive bays	
	2x 3.5" Hot-swap SATA HDD trays
Power Supply	
	1280W Redundant High-efficiency Digital Power Supplies w/ PMBus 1.2
Cooling System	
	8x 8cm heavy duty fans with air shroud and PWM fan speed control
Form Factor	
	4U Rackmount Width- 17.63" (448mm), Height- 6.96" (177mm) , Depth – 29" (737mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit www.tyronesystems.com</p>	