

# Tyrone Camarero Specifications



## Camarero IDI200C2R-28

### Key features

- Eagle Stream based server featuring future Intel® Xeon® Scalable “Sapphire Rapids” processors
- Up to 12 TB memory capacity, 32 DIMMs per system DDR5, Support for new Intel® Optane™ persistent memory 300 series (Crow Pass), 4800 MT/s (RDIMM, 1DPC)
- Up to 6 FH & 1 HH PCIe 5.0, 1 HH PCIe 5.0 (x32 riser 1 PCIe 5.0, x32 riser 2 PCIe 5.0, x16 riser 3 PCIe 5.0)
- 8 x 2.5” bays SAS/SATA
- 8 SATA 6Gbps ports
- 2x10GBase-T, 4x25GbE SFP+, 2x100GbE SFP2
- 1300/1600/2100W Power supply
- 2U Rackmount



### Processor/Cache

Processor Eagle Stream based server featuring future Intel® Xeon® Scalable “Sapphire Rapids” processors

### System Memory

Memory Capacity Up to 12 TB memory capacity, 32 DIMMs per system DDR5, Support for new Intel® Optane™ persistent memory 300 series (Crow Pass), 4800 MT/s (RDIMM, 1DPC)

### Expansion Slots

PCI-Express Up to 6 FH & 1 HH PCIe 5.0, 1 HH PCIe 5.0 (x32 riser 1 PCIe 5.0, x32 riser 2 PCIe 5.0, x16 riser 3 PCIe 5.0)

### Integrated Onboard

Onboard Storage Dual M.2 SATA/PCIe 80/110mm connectors

LAN 2x10GBase-T, 4x25GbE SFP+, 2x100GbE SFP2

### Add-on Options

Optical Drive None

### Drive Bays

HDD Bays 8 x 2.5” SAS/SATA

### Power Supply

1300/1600/2100W Power supply

### Form Factor

Form Factor 2U Rackmount

Dimensions Depth : 30"

Email : [info@tyronesystems.com](mailto:info@tyronesystems.com)

For more/current product information, visit  
[www.tyronesystems.com](http://www.tyronesystems.com)