

Tyrone Camarero Specifications

Camarero- JS12E1R-212R

Key Feature

Cloud Backup, Data Replication, or High Density Archive Storage Applications

- 2U Storage JBOD Chassis with capacity 12 x 3.5" hot-swappable HDDs bays
- Single Expander Backplane Boards support SAS3/2 or SATA3 HDDs with 12Gb/s throughput
- 4 x Mini-SAS HD ports for Internal / External Cascading Expander Combination for high performance, high availability or high redundancy requirements
- 1x IPMI port for Remote System Power on/off and system monitoring
- Support NTP for time synchronization & RTC battery backup
- 600W (1+1) 94% efficient Platinum level power supplies
- 3 x 80mm high efficient hot-swappable fans for best system cooling
- Dual LAN with 10GBase-T with Intel® X550
- Ideal for Cloud backup, data Replication or High desnsity Archive Storage Applications



Backplane	
Backup	12-Port 2U SAS3 12Gbps single-expander backplane, support up to 12x 3.5-inch SAS3/SATA3 HDD/SSD
Drive bays	
HDD Bays	12x 3.5" hot-swap HDD bay for JBOD solution
Front Panel	
LEDs	1 Network Activity LEDs
Buttons	Power On/Off button, System Reset Button, Unit Identification (UID) button

Power Supply	
Power Supply	600W / 650W Redundant Power Supply
Cooling System	
Fans	3x 80x38mm hot-swap cooling fan(s)
Form Factor	
Form Factor	2U JBOD storage chassis
Dimensions	
Dimensions	(L x W x H) -336 x 76 x 40 mm
<p>Email : Info@tyronesystems.com For more/current product information, Visit www.tyronesystems.com</p>	