

# Tyrone Camarero Specifications

# Tyrone

## Camarero: MSA200A2N-28

### Key Feature

A high-performance single-socket AMD EPYC™ 9004/9005 platform optimized for PCIe Gen5 I/O, dual OCP 3.0 networking, high-density DDR5 memory, NVMe storage, and enterprise-grade security with hardware Root of Trust.

- Support Single AMD EPYC™ 9004/9005 Series processor with high-core-count architecture
- Supports 24 x DDR5 RDIMM Expandable Memory
- 2 x PCIe Expansion Slots
- 2 x PCIe 5.0 x16 OCP3 NIC Mezzanine slot
- Integrated ASPEED BMC Controller
- Dual BIOS & BMC
- Supports IPMI, Redfish, remote KVM, and virtual media
- 80+ Titanium CRPS Power Supply for high efficiency and redundancy
- Enhanced Security with TPM 2.0 and Chassis Intrusion detection
- Hardware Root of Trust (RoT)
- Supports 2 x 400W Passive GPUs



Processor/Cache	
<b>Processor</b>	Support Single AMD EPYC™ 9004 and 9005 series processor, Upto 500W TDP, (LGA 6096)
System Memory	
<b>Memory Capacity</b>	24 x DDR5 DIMM Slots 12 channels(2DPC), RDIMM/RIMM-3DS Max. Frequency 5200MT/s(1DPC), 4400MT/s(2DPC)* *Subject to CPU & Memory Configuration. Max. Capacity per DIMM: 256GB Max System Memory : 6TB
Expansion Slot	
<b>PCI-Express</b>	2 x PCIe 5.0 x16 FHFL dual wide slot 2 x PCIe 5.0 x16 OCP 3.0 slot
Indicators/LEDs	
<b>Indicators /LEDs</b>	1 x Power button with LED (Rear/Front) 1 x UID button with LED (Rear/Front) 1 x Reset Button (Front) 4 x Status LEDs : LAN/M.2/Fault(Front/Rear)
Security	
<b>Security</b>	Chassis intrusion TPM 2.0 (Optional) Hardware Root of Trust (RoT)
Environment	
<b>Environment</b>	System Operating Temperature: 0°C ~ 35°C Non-operating Temperature: -20°C ~ 70°C Non-operating Relative Humidity: 5% to 85% (non-condensing)

Ports	
<b>Ports</b>	1 x 1000Base-T Dedicated Server Management Port (Rear) 2 x USB 3.0 Type-A Port (Front) 1 x Mini-DP Display Port (Rear) 1 x COM USB Type A Port (Rear) 1 x USB 2.0 Type-A Port (Rear)
Drive bays	
<b>HDD Bays</b>	8 x 2.5" U.2 PCIe 5.0 x4 Hot Swap NVMe drive bays 2 x 2280/22110 PCIe 3.0 x2 NVMe M.2 drive bays
Power Supply	
<b>Power Supply</b>	(1+1) 2400W 80+ CRPS Titanium Redundant Power Supply
Form Factor	
<b>Form Factor</b>	2U Rackmount
Dimensions	
<b>Dimensions</b>	438mm (W) x 87mm (H) x 764mm (D)
<p><b>Email : <a href="mailto:Info@tyronesystems.com">Info@tyronesystems.com</a></b></p> <p><b>For more/current product information, Visit <a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b></p>	

• AMD the AMD logo inside are trademarks of Advanced Micro Devices in US and / Or other Countries  
• Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks . All other brands and names are the property of their respective owners