

# Tyrone Camarero Specifications

Tyrone

## Camarero: MSI300A3R-212

### Key Feature

The MSI300A3R-212 is a 2U rackmount server powered by Intel® Xeon® 6700-series processors, featuring high-bandwidth DDR5 memory, PCIe Gen5 expansion slots, Hot-Swap SAS/SATA Drives, Dual 10GbE RJ45 networking, and redundant Titanium/Platinum-rated power supplies.

- Supports Single Intel® Xeon® 6700E, 6500P and 6700P-Series Processors
- Supports 8 x DDR5 RDIMM Expandable Memory
- 4 x PCIe 5.0 x16 Expansion slots
- Integrated ASPEED BMC Controller
- Supports IPMI, Redfish, remote KVM, and virtual media
- Enhanced Security with TPM 2.0 and Chassis Intrusion
- 80+ Titanium/Platinum Redundant Power Supply



Processor/Cache		Indicators/LEDs
<b>Processor</b>		<b>Indicators/LEDs</b>
Single Intel® Xeon® 6700E, 6500P and 6700P-Series Processors, Upto 350W TDP(LGA 4710 (Socket E2))		1 x Power Button (Front) 1 x UID Button with LED (Front/Rear) 1 x System Alert LED (Front) 1 x System Reset Button (Front) 1 x LAN LED (Front) 1 x Drive Activity LED (Front)
System Memory		Drive bays
<b>Memory Capacity</b>		<b>HDD Bays</b>
8 DDR5 DIMM slots, 8 Channels (1DPC), DDR5 288-pin RDIMM, RDIMM : 256GB (6400MT/s), MCRDIMM: 64GB (8000MT/s) <b>Max. Capacity per DIMM:</b> 256GB(RDIMM) <b>Max System Memory :</b> 2TB		Supports 12 x hot-swap 2.5"/3.5" SAS/SATA drive bays(Front) 2 x 2280/22110 PCIe 5.0 x2 NVMe M.2 ports (On Board)
Expansion Slot		Security
<b>PCI-Express</b>		<b>Security</b>
4 x PCIe 5.0 x16 HHFL slots(R1S CPU required to enable all Slots, otherwise only 3 will be working) 6 x PCIe 5.0 x8 MCIO 8i connectors(R1S CPU required to enable all Connector, otherwise only 2 will be working)		Chassis intrusion TPM 2.0
Ports		Environment
<b>Ports</b>		<b>Environment</b>
1 x 1000Base-T Dedicated Server Management Port (Rear) 2 x 10GbE (RJ45) by Intel X710-AT2 (Rear) 1 x DB-15 VGA Port (Rear) 1 x DB9 COM Port (Rear) 1 x 2.1 ch audio Ports (Rear) 2 x USB 3.2 Gen 1 Type-A Ports (Rear) 2 x USB 3.2 Gen 1 Type-A ports (Front)		System Operating Temperature: 10°C ~ 35°C Non-operating Temperature: -40°C ~ 70°C <b>Non-operating Relative Humidity:</b> 20% to 90% (non-condensing)
Power Supply		Form Factor
<b>Power Supply</b>		<b>Form Factor</b>
(1 + 1) 800W/1300W 80+ Redundant Power Supply		2U Rackmount
Dimensions		Dimensions
		436mm (W) x 87mm (H) x 660mm (D)
<b>Email : <a href="mailto:Info@tyronesystems.com">Info@tyronesystems.com</a></b> <b>For more/current product information, Visit <a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b>		