

Tyrone Camarero Specifications



Camarero QS200T3R-26R

Key features

- Quad socket R (LGA 2011) supports Intel® Xeon® processor E5-4600 v2 (12-Core)** or E5-4600 (8-Core) family, w/ QPI up to 8.0 GT/s
- Up to 1TB* DDR3 1600MHz ECC Registered DIMM; 32x DIMM sockets * Depends on memory configuration
- 4x PCI-E 3.0 x16 (2 in x8) LP Slots
- Intel® i350 Dual port GbE LAN
- I/O ports: 2x GbE LAN, 1x Dedicated LAN for IPMI Remote Management, 1x VGA, 1x COM port, 4x USB 2.0
- 6x 3.5" Hot-swap SATA3 Drive Bays
- 3x 8cm Hot-swap Cooling Fans
- 1400W Redundant Digital PS, 80 PLUS, Platinum Level (94%)



Processor/Cache	
Processor	Quad socket R (LGA 2011) supports Intel® Xeon® processor E5-4600 v2 (12-Core)** or E5-4600 (8-Core) family, w/ QPI up to 8.0 GT/s
Chipset	
Intel® C602 Chipset	
System Memory	
Memory Capacity	32x 240-pin DDR3 DIMM sockets Supports up to 1TB DDR3 ECC Registered memory (RDIMM) in 32 DIMM sockets
Expansion Slots	
PCI-Express	4x PCI-E 3.0 x16 (2 in x8) Low-profile Slots
Integrated On-Board	
SATA	SATA 2.0 3Gbps with RAID 0, 1, 5, 10 SATA 3.0 6Gbps with RAID 0, 1
LAN	2x RJ45 Gigabit Ethernet LAN ports 1x dedicated LAN port for IPMI
Add-on Options	
RAID Card	Optional
Optical Drive	Optional

Front Panel :	
LED Indicators	Power LED Hard drive activity LED 2x Network activity LEDs System Overheat LED
Switches	Power On/Off button System Reset button
Drive bays	
HDD bays	6x 3.5" Hot-swap SATA3 Drive Bays
Peripheral Bays	1x Slim DVD-ROM (Optional)
Power Supply	
1400W Redundant Digital PS, 80 PLUS, Platinum Level (94%)	
Cooling System	
3x 8cm Hot-swap Cooling fans 1x Air Shroud	
Form Factor	
2U Rackmount	
Height	3.5" (89mm)
Width	17.2" (437mm)
Depth	27.9" (709mm)
<p>E : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	