

Tyrone Camarero Specifications

Tyrone[®]

Camarero QS300TR-26R4

Key features

- Quad socket R1 (LGA 2011) supports Intel® Xeon® processor E7-8800 v4/v3, E7-4800 v4/v3 family.
- Intel® C602J chipset
- Up to 2TB DDR4 (64GB LRDIMM), up to 1866MHz; 32x DIMM slots
- 2x PCI-E 3.0 x16 Low-profile slot; 2x PCI-E 3.0 x8 Low-profile slot
- Intel® i350 Dual port GbE LAN
- I/O ports: 2x GbE LAN, 1x Dedicated LAN for IPMI Remote Management
1x VGA, 1x COM port, 3x USB 2.0
- 6x 3.5" Hot-swap SATA Drive Bays
- 3x 8cm Heavy Duty fans w/ speed control
- 1400W Redundant Digital PS Platinum Level (95%)



Processor/Cache		Front Panel	
Processor	Quad socket R1 (LGA 2011) supports Intel® Xeon® processor E7-8800 v4/v3, E7-4800 v4/v3 family.	LED Indicators	Power LED, Hard drive activity LED, 2x Network activity LEDs, System Overheat LED
Chipset	Intel® C602J chipset	Buttons	Power On/Off button, System Reset button
System Memory		Drive Bays	
Memory Capacity	32x 288-pin DDR4 DIMM slots, Supports up to 2TB DDR4 ECC LRDIMM in 32 DIMM slots	HDD bays	6x 3.5" Hot-swap Drive Bays
Expansion Slots		Power Supply	
PCI-Express	2x PCI-E 3.0 x16 Low-profile slot 2x PCI-E 3.0 x8 Low-profile slot		1400W Redundant Digital PS Platinum Level (95%)
Integrated On-Board		Cooling System	
SATA	SATA2 (3Gbps) with RAID 0, 1, 5, 10. SATA3 (6Gbps) with RAID 0, 1		3x 8cm Hot-swap Cooling fans. 1x Air Shroud
LAN	2x RJ45 Gigabit Ethernet LAN ports, 1x dedicated LAN port for IPMI	Form Factor	
Add-on Options		Form Factor	2U Rackmount
Raid	Optional	width:	17.2" (437mm),
Optical Drive	None	Height:	3.5" (89mm),
		Depth:	27.9" (709mm)
		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	