Tyrone Camarero Specifications

Camerero QS300TR-424RTL

Key features

- Quad socket R1 (LGA 2011) supports Intel® Xeon® processor E7-8800 v4/v3, E7-4800 v4/v3 family (up to 24-Core)
- Intel® C602J chipset
- Up to 12TB DDR4 (128GB 3DS LRDIMM); 96x DIMM slots (8x memory module boards: X10QBi-MEM2)
- Up to 11x PCI-E 3.0 slots (4 x16, 7 x8)
- I/O ports via Add-on Card: 2x 10Gb LAN, 1x Dedicated LAN for IPMI Remote Management, 1x VGA
- Up to 24x 3.5" Hot-swap drive bays
- 4x 92mm Hot-swap cooling fans, 3x 80mm Hot-swap rear exhaust fans, 2x 80mm rear exhaust fans (option)
- 1620W Redundant (N+1) Power Supplies, Platinum Level (94%)







Processor/Cache

Processor Quad socket R1 (LGA 2011) supports

Intel® Xeon® processor E7-8800 v4/v3, E7-4800 v4/v3 family (up to 24-Core)

Chipset

Chipset Intel® C602J chipset

System Memory

Memory Capacity 96x 288-pin DDR4 DIMM slots, Supports

up to 12TB DDR4 ECC 3DS LRDIMM in

96 DIMM slots

Expansion Slots

PCI-Express Up to 11x PCI-E 3.0 slots (4 x16, 7 x8)

Integrated On-Board

SATA SATA3 (6Gbps) with RAID 0, 1,SATA2

(3Gbps) with RAID 0, 1, 5, 10

LAN 2x RJ45 10GBase-T ports on AOM,

1x dedicated LAN port for IPMI on AOM

Add-on Options

Raid Card Optional

Optical Drive None

Front Panel

LED Indicators CPU / System Overheat LED

Drive Bays

HDD bays 24x 3.5" drive bays. BPN-SAS-846A direct

attached backplane, system supports up to 24 HDDs by using selected RAID/HBA card and default HDD connection is onboard C602J chipset 2 SATA3 + 4 SATA2

Power Supply

1620W Redundant (N+1) Power Supplies, Platinum Level (94%)

Cooling System

4x 92mm Hot-swap cooling fans, 3x 80mm Hot-swap rear exhaust fans,2x 80mm rear exhaust fans (option)

Form Factor

Form Factor 4U Rackmount

Width: 17.2" (437mm), Height: 7.0" (178mm), Depth: 32.1" (815mm)

Email: info@tyronesystems.com
For more/current product information, visit
www.tyronesystems.com