

Tyrone Camarero Specifications

Tyrone

Camarero: RDA200A2G-424

Key Feature

- Dual AMD EPYC™ 9005/9004 series processors
- 8 x NVIDIA H200 NVL or RTX PRO 6000 Blackwell Server Edition PCIe GPU cards
- Supports 12+12 DDR5 RDIMM Expandable Memory
- 10 x PCIe 5.0 Expansion Slots
- Latest Aspeed AST2600 BMC Controller
- Support 4 x 2.5" NVMe + 20 x 2.5" SATA/SAS Hot Swappable Drives
- 80+ Titanium CRPS Power Supply
- Enhanced Security with TPM 2.0



Processor/Cache		Indicator	
Processor	Supports Dual AMD EPYC™ 9005/9004 series processors Upto 500W TDP (LGA 6096)	Indicators	1 x Power LED Button (Front) 1 x UID LED Button (Front) 1 x System Fault LED (Front) 24 x HDD LED (Front)
System Memory		Security	
Memory Capacity	Supports 12+12 DDR5 Expandable Memory, Max Frequency : RDIMM : 6400MHz(1DPC) Max. Capacity per DIMM : 256GB(RDIMM), Upto 6TB System Memory	Security	TPM 2.0
Expansion Slot		Power Supply	
PCI-Express	8 x16 PCIe5.0 FHFL (Double Width) 1 x8 PCIe5.0 FHHL (Single Width) 1 x8 PCIe5.0 OCP NIC 3.0	Power Supply	2700W (3+1) 80+ CRPS Titanium Certified
Ports		Form Factor	
Ports	1 x 1000Base-T Dedicated Server Management Port (Rear) 2 x 1GBase-T Ethernet ports with Intel® i350 (Rear) 2 x USB 3.2 Gen1 Type-A Port (Rear) 4 x USB 3.2 Gen1 Type-A Port (Front) 1 x Display port DB15 (Rear)	Form Factor	4U Rackmount
Environment		Dimensions	
Environment	System Operating Temperature: 0°C ~ 35°C Non-operating Temperature: -20°C ~ 70°C Non-operating Relative Humidity: 5% to 85% (non-condensing)	Dimensions	438mm(W) x 176mm(H) x 786mm(D)
		Email : Info@tyronesystems.com For more/current product information, Visit www.tyronesystems.com	

• AMD the AMD logo inside are trademarks of Advanced Micro Devices in US and / Or other Countries
• Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks . All other brands and names are the property of their respective owners