

# Tyrone Camarero Specifications

# Tyrone

## Camarero: RDA200A3R-212

### Key Feature

- Supports Dual AMD EPYC 9005/9004 Processors
- Supports 8+8 DDR5 RDIMM Expandable memory
- 5 x x16 Expansion slots
- Latest AST2600 BMC Controller iKVM, vMedia support
- Supports 12 x 3.5"/2.5" Hot Swappable Drives
- Dual 10 GbE (RJ45) by Intel X710-AT2
- Multiple PSU options 800W/1300W/1600W CRPS 80+



Processor/Cache		Front LEDs	
Processor	Supports Dual AMD EPYC 9005/9004 Processors upto 360W TDP	Front LEDs	1 x Power Status 1 x HDD Activity 2 x LAN Activity 1 x UID LED
System Memory		Drive bays	
Memory Capacity	Supports 8+8 DDR5 RDIMM Expandable memory (1DPC) Max Frequency 6400 MHz	HDD Bays	Support 8 x (SAS/SATA) + 4 x (SAS/SATA/NVMe) 3.5"/2.5" Hot Swappable Bays
Expansion Slot		Power Supply	
PCI-Express	2 x16 PCIe5.0 + 3 x16 PCIe4.0 3 x MCIO PCIe 5.0 x8	Power Supply	800W/1300W/1600W 80+ CRPS
Ports		Security	
Front Ports	2 x USB 3.0 Type A Ports	TPM	TPM 2.0
Rear Ports	1 x RJ45 GbE connector for BMC dedicate management port (RTL8211E) 2 x 10GbE (RJ45) by Intel®X710-AT2 2 x USB3.2 Gen1 type-A Ports 1 x DB-15 VGA connector 1 x external UID/switch button	Form Factor	
		Form Factor	2U Rackmount
		Dimensions	
		Dimensions	660 x 436 x 87 mm
		Email : <a href="mailto:Info@tyronesystems.com">Info@tyronesystems.com</a> For more/current product information, Visit <a href="http://www.tyronesystems.com">www.tyronesystems.com</a>	