Tyrone Camarero Specifications

Tyrone

Camerero: RDA200A3R-28

Key Feature

- Supports Dual AMD EPYC 9005/9004 Processors
- Supports 8+8 DDR5 RDIMM Expandable memory
- 5 x x16 Expansion slots
- Latest AST2600 BMC Controller iKVM, vMedia support
- Supports 8 x 3.5"/2.5" Hot Swappable Drives
- Dual 10 GbE (RJ45) by Intel X710-AT2
- Multiple PSU options 800W/1300W/1600W CRPS 80+

EPYC

Processor/Cache

Processor	Supports Dual AMD EPYC 9005/9004 Processors upto 360W TDP

System Memory

Memory Capacity	Supports 8+8 DDR5 RDIMM Expandable memory (1DPC) Max Frequency 6400 MHz

Expansion Slot

PCI-Express	2 x16 PCIe5.0 + 3 x16 PCIe4.0 3 x MCIO PCIe 5.0 x8

Ports

Front Ports	1 x USB 3.0 Type A Ports
Rear Ports	1 x RJ45 GbE connector for BMC dedicate management port (RTL8211E) 2 x 10GbE (RJ45) by Intel®X710-AT2 2 x USB3.2 Gen1 type-A Ports 1 x DB-15 VGA connector 1 x external UID/switch button

Front LEDs

Front LEDs	1 x Power Status 1 x HDD Activity 1 x LAN Activity 1 x Alert LED 1 x UID LED

Drive bays

HDD Bays	Support 8 x (SAS/SATA) 3.5"/2.5" Hot Swappable Bays 4 x 2.5" internal drives 1 x slim DVD-ROM

Power Supply

Power Supply	800W/1300W/1600W 80+ CRPS

Security

TPM	TPM 2.0

Form Factor

Form Factor	2U Rackmount

Dimensions

Dimensions	680 x 430 x 88 mm

Email : Info@tyronesystems.com

For more/current product information, Visit

www.tyronesystems.com