# **Tyrone Camarero Specifications**

## Camarero: RDA200A3S-436

## **Key Feature**

The RDA200A3S-436 Storage Server is designed for scalable, high-throughput storage deployments in data center and edge environments. It supports modular expansion, Latest Generation AMD 9004/9005 dual CPUs, and flexible I/O fabrics to deliver predictable performance at scale. Leveraging state-of-the-art PCIe Gen5 integration and multi-tier storage architecture, the system enables seamless scaling from capacity-centric workloads to latency-sensitive access patterns.

- Supports Dual AMD EPYC 9004/9005 Processors
- Supports 8+8 DDR5 RDIMM Expandable Memory
- 5 x16 PCle Expansion Slots
- Latest AST2600 BMC Controller iKVM, vMedia support
- Support 36 x 2.5"/3.5" Data drives + 2 x 2.5" hot-swap OS drives
- Dual 10GbE(RJ45) by Intel®X710-AT2
- 1300W 80+ Titanium Redundant Power Supply











Р	r	0	С	е	S	S	0	r

Supports Dual AMD EPYC 9004/9005 Processor

CPUs of TDP upto 300W (SP5-LGA

6096)

#### System Memory

Memory Supports 8+8 DDR5 RDIMM Capacity

Expandable Memory, Max Frequency 6400MHz

Max Capacity 256GB/DIMM, Max System Memory 4TB(3DS RDIMM)

#### **Expansion Slot**

**PCI-Express** 3 x16 PCle5.0 + 2 x16 PCle4.0(HHFL)

#### **Ports**

**Ports** 1 x RJ45 GbE connector for BMC

> dedicate management port (RTL8211E) 2 x 10GbE (RJ45) by Intel®X710-AT2 2 x USB 3.0 Type A Ports (Front) 2 x USB 3.2 Gen 1 Type A Ports (Rear)

1 x DB-15 VGA connector 1x external UID/switch button

#### **Environment**

**Temperature** Operating Temperature: 10°C ~ 35°C

Non Operating Temperature: 40°C ~

Humidity Non operation humidity: 20% ~ 90%

(Non-condensing)

#### Front Panel

I FD 1x Power LED Button

1x Alert LED

1 x HDD Activity LED 1 x LAN Activity LED 1x Reset Button 1x UID LED Button

#### Drive bays

**HDD Bays** Supports 36 x 2.5"/3.5" Hot Swappable

Bays (24Bay 12G + 12Bay 12G expander

controller based backplane)

Supports 2 x 2.5" hot-swap SATA OS

drives (7mm)

Supports 2 x M.2 2280/22110 PCle

Gen4.0 x4 (Onboard)

## Security

Security **TPM 2.0** 

## **Power Supply**

**Power Supply** 1300W 80+ Titanium Redundant Power

Supply

#### Form Factor

Form Factor 4U Rackmount

**Gross Weight** 42 Ka

**Dimensions** 680(L) x 430(W) x 174(H) mm

Email: Info@tyronesystems.com For more/current product information, Visit www.tyronesystems.com

AMD the AMD logo inside are trademarks of Advanced Micro Devices in US and / Or other Countries
Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners