

Tyrone Camarero Specifications

Tyrone

Camarero: RDI300A2G-424

Key Feature

- Dual Intel® Xeon® 6700P, 6500P and 6700E-series processors Upto 350W TDP
- 8 x NVIDIA H200 NVL or RTX PRO 6000 Blackwell Server Edition PCIe GPU cards
- Supports 16+16 DDR5 RDIMM Expandable Memory
- 10 x PCIe 5.0 Expansion Slots
- Latest Aspeed AST2600 BMC Controller
- Support 4 x 2.5" NVMe + 20 x 2.5" SATA/SAS Hot Swappable Drives
- 80+ Titanium CRPS Power Supply
- Enhanced Security with TPM 2.0



Processor/Cache		Front Panel	
Processor	Supports Dual Intel® Xeon® 6700P, 6500P and 6700E-series processors Upto 350W TDP (LGA 4710)	Ports	1 x 1000Base-T Dedicated Server Management Port (Rear) 2 x 1GBase-T Ethernet ports with Intel® i350 (Rear) 2 x USB 3.2 Gen1 Type-A Port (Rear) 4 x USB 3.2 Gen1 Type-A Port (Front) 1 x Display port DB15 (Rear)
System Memory		Drive bays	
Memory Capacity	Supports 16+16 DDR5 Expandable Memory, Max Frequency : RDIMM : 6400MHz(1DPC), 5200MHz(2DPC), MRDIMM : 8000MT/s (1DPC only) Max. Capacity per DIMM : 128GB(RDIMM), Upto 4TB System Memory, MRDIMM : 64GB	HDD Bays	Support 4 x 2.5" NVMe + 20 x 2.5" SATA/SAS* Hot Swappable Drives (*RAID/HBA Card Required for SAS/SATA Support) Backplane : 24 x SAS/SATA/NVMe Passive(Configurable) 1 x M.2 PCIe5.0 x4 of form factor 22110/2280
Expansion Slot		Security	
PCI-Express	8 x16 PCIe5.0 FHFL (Double Width) 1 x16 PCIe5.0 FHHL (Single Width) 1 x8 PCIe5.0 FHHL (Single Width)	Security	TPM 2.0
Indicators		Power Supply	
Indicators	1 x Power LED Button (Front) 1 x UID LED Button (Front) 1 x System Fault LED (Front) 24 x HDD LED (Front)	Power Supply	2700W (3+1) 80+ CRPS Titanium Certified
Environment		Form Factor	
Environment	System Operating Temperature: 0°C ~ 35°C Non-operating Temperature: -20°C ~ 70°C Non-operating Relative Humidity: 5% to 85% (non-condensing)	Form Factor	4U Rackmount
		Dimensions	
		Dimensions	438mm(W) x 176mm(H) x 786mm(D)
<p>Email : Info@tyronesystems.com</p> <p>For more/current product information, Visit</p> <p>www.tyronesystems.com</p>			