

Tyrone Camarero Specifications

Tyrone

Camarero: RSA210F0A-55

Key Feature

- Supports Single AMD EPYC™ 4005/4004 and AMD Ryzen™ 9000/8000/7000 Series Processors
- Supports 4(2DPC) x DDR5 ECC/non-ECC UDIMM Expandable Memory
- 3 x PCIe Expansion Slots
- Latest Aspeed AST2600 BMC Controller
- Support 5 x 2.5"/3.5" SAS/SATA Fix Drives
- Supports 4 X 5.25" ODD + 1 x 3.5" Disk
- 80+ Platinum CRPS & ATX Power Supply
- Enhanced Security with TPM 2.0 and Chassis Intrusion



Processor/Cache	
Processor	Single AMD EPYC™ 4005/4004 and AMD Ryzen™ 9000/8000/7000 Series
Chipset	
Chipset	AMD B650E
System Memory	
Memory Capacity	4(2DPC) x DDR5 ECC/non-ECC UDIMM Expandable Memory Max Frequency : 5600 MHz (1DPC); 3600 MHz (2DPC) Max Capacity/DIMM : 48GB
Expansion Slot	
PCI-Express	1x16 PCIe5.0 FHFL Slot 1x4 PCIe 5.0 FHFL Slot 1x1 PCIe 4.0 FHFL Slot
Ports	
Ports	2 x RJ45 (1GbE) by Intel® i210 1 x DB15 (VGA) 1 x DisplayPort 1 x HDMI Port 1 x DB9 (COM) 4 x USB 3.2 Gen1 (Rear) 2 x USB 3.2 Gen1 (Front) 1 x RJ45 (1GbE) RTL8211F Dedicated IPMI Port
Security	
Security	Chassis Intrusion TPM 2.0
Indicators	
Indicators	1 x Power status Button/LED 1 x HDD 2 x LANs 1 x System fail LEDs 1 x UID LED (Front) 1 x UID button w/ LED(Rear)
Power Supply	
Power Supply	800W 80+ CRPS OR 500W/1200W ATX PSU
Environment	
Environment	System Operating Temperature: 0°C ~ 35°C Non-operating Temperature: -20°C ~ 70°C Non-operating Relative Humidity: 5% ~ 85% (non-condensing)
Form Factor	
Form Factor	5U Rackmount/Tower
Dimensions	
Dimensions	430mm(W) x 200mm(H) x 560mm(D)
Email : Info@tyronesystems.com For more/current product information, Visit www.tyronesystems.com	