

Tyrone Camarero Specifications

Tyrone

Camerero: RSI200A3A-48

Key Feature

- Single Intel® Xeon® W-2500/2400 and W-3500/3400 series processors
- Intel® W790
- 8 x DDR5 4400MT/s (2DPC) / 4800MT/s (1DPC)
- 4 x16 PCIe5.0
- Intel® W790 (Up to 8 SATA 6Gb/s; RAID 0/1/5/10) : 1 OCuLink for 4 SATA + 4 SATA 7-pin
- 1 x RJ45 GbE connector for BMC dedicate management port, 2 x 10GbE (RJ45),1 x 2.5GbE (RJ45) ,1 x 1GbE (RJ45) 2 x USB3.2 Gen1 type-A Port, 1 x DB-15 VGA connector, 1 x DB9 COM connector, 1 x USB 3.2 Gen1 Header to support two Front USBs, 1 x external UID/switch button
- 8 x Hot-swap 3.5"/2.5" drive bays SAS/SATA, 2 x M.2 SSD 2280 PCIe4.0 x4
- 1300/1600 80+ Redundant Power Supplies



Processor/Cache		Drive bays	
Processor	Single Intel® Xeon® W-2500/2400 and W-3500/3400 series processors	HDD Bays	8 x Hot-swap 3.5"/2.5" drive bays SAS/SATA, 2 x M.2 SSD 2280 PCIe4.0 x4
Chipset		Power Supply	
Chipset	Intel® W790	Power Supply	1300/1600 80+ Redundant Power Supplies
System Memory		Form Factor	
Memory Capacity	8 x DDR5 4400MT/s (2DPC) / 4800MT/s (1DPC)	Form Factor	4U Rackmount
Expansion Slot		Dimensions	
PCI-Express	4 x16 PCIe5.0	Dimensions	680 x 438 x 175 mm
Ports		Email : Info@tyronesystems.com For more/current product information, Visit www.tyronesystems.com	
Ports	1 x RJ45 GbE connector for BMC dedicate management port, 2 x 10GbE (RJ45),1 x 2.5GbE (RJ45) ,1 x 1GbE (RJ45) 2 x USB3.2 Gen1 type-A Port, 1 x DB-15 VGA connector, 1 x DB9 COM connector, 1 x USB 3.2 Gen1 Header to support two Front USBs, 1 x external UID/switch button		

◦ Intel, the Intel logo,the Intel Inside logo,Xeon,and Intel Xeon Phi are trademarks of Intel Corporation in the U.S and /Or other Countries
◦ Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the properties of their respective owners