

Tyrone Camarero Specifications

Tyrone

Camarero: RSI20F0A-55

Key Feature

- Single Intel® Xeon® W-2500/2400 and W-3500/3400 series processors
- Intel® W790
- 8 x DDR5 4400MT/s (2DPC) / 4800MT/s (1DPC)
- 4 x16 PCIe5.0
- Intel® W790 (Up to 8 SATA 6Gb/s; RAID 0/1/5/10) : 1 OCuLink for 4 SATA + 4 SATA 7-pin
- 1 x RJ45 GbE connector for BMC dedicate management port, 2 x 10GbE (RJ45),1 x 2.5GbE (RJ45) ,1 x 1GbE (RJ45) 2 x USB3.2 Gen1 type-A Port, 1 x DB-15 VGA connector, 1 x DB9 COM connector, 1 x USB 3.2 Gen1 Header to support two Front USBs, 1 x external UID/switch button
- 5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x5
- Front: 120 x 25 mm x1 PWM Fan,Rear: 120 x 25 mm x1 PWM Fan
- 50/1200W Redundant Power Supply
Optional : 500/1200W Single Power Supply



Processor/Cache		Drive bays	
Processor	Single Intel® Xeon® W-2500/2400 and W-3500/3400 series processors	HDD Bays	5.25" x 4, 3.5" x 1; Internal: 3.5" x 5 or 2.5" x5
Chipset		Power Supply	
Chipset	Intel® W790	Power Supply	550/1200W Redundant Power Supply Optional : 500/1200W Single Power Supply
System Memory		Cooling System	
Memory Capacity	8 x DDR5 4400MT/s (2DPC) / 4800MT/s (1DPC)	Front	120 x 25 mm x1 PWM Fan
Expansion Slot		Rear	120 x 25 mm x1 PWM Fan
PCI-Express	4 x16 PCIe5.0	Form Factor	
Ports		Form Factor	5U Rackmount/ Tower
Ports	1 x RJ45 GbE connector for BMC dedicate management port, 2 x 10GbE (RJ45), 1 x 2.5GbE (RJ45) , 1 x 1GbE (RJ45) 2 x USB3.2 Gen1 type-A Port, 1 x DB-15 VGA connector, 1 x DB9 COM connector, 1 x USB 3.2 Gen1 Header to support two Front USBs, 1 x external UID/switch button	Dimensions	
		Dimensions	Height:7.0" (178mm),Width:17.6" (447mm),Depth:31.7" (805mm)
		Email : Info@tyronesystems.com For more/current product information, Visit www.tyronesystems.com	