Tyrone Camarero Specifications Camarero SA720TT-212R

Key features

- Compute Intensive Applications, HPC, Data Center, Enterprise Server, Hyperscale / Hyperconverged
- Four hot-pluggable systems (nodes) in a 2U form factor.
- Single AMD EPYC™ 7002/7000 Series Processor, Up to 64 Cores.
- System on Chip
- Up to 2TB ECC 3DS LRDIMM, up to DDR4-3200MHz; 8 DIMM slots
- 2 PCI-E 4.0 (x16) Low-profile slots, 1 SIOM card support(must bundle with network card)M.2 Interface: 1 SATA/PCI-E 3.0 x4 Form Factor: 2280, 22110,Key: M-key
- Integrated IPMI 2.0 + KVM with dedicated LAN.
- 3 Hot-swap 3.5" SATA3 drive bays, M.2 Interface: 4 SATA/PCI-E 3.0 x4, M.2 Form Factor: 2280, 22110, 2260, 2242, M.2 Key: M-key
- Video via Aspeed AST2500 BMC
- 4 Heavy duty 8cm PWM fans
- 2000W Redundant Power Supplies with PMBus







			Ca	

Single AMD EPYC™ 7000/7002 Series Processor

Processor, Up to 64 Cores

Note * Please contact Tyrone Technical Support

for specifics on high power processor

support

Chipset

Chipset System on Chip

System Memory

Memory Capacity Up to 2TB ECC 3DS LRDIMM,up to

DDR4-3200MHz; 8 DIMM slots

Expansion Slots

PCI-Express 2 PCI-E 4.0 (x16) Low-profile slots,

1 SIOM card support(must bundle with

network card)M.2

Interface: 1 SATA/PCI-E 3.0 x4 Form Factor: 2280, 22110, Key: M-k

Integrated On-Board

SATA SATA3 (6 Gbps)

LAN Provided via SIOM,1 RJ45 Dedicated

IPMI LAN port

Add-on Options

Raid Card None

Optical Drive None

Front Panel

LED Power status LED, HDD activity LED,

Network activity LEDs,

Universal Information (UID) LED

Buttons Power On/Off button, UID button

Drive Bays

HDD Drives 3 Hot-swap 3.5" SATA3 drive bays

Power Supply

2000W Redundant Power Supplies with PMBus

Cooling System

4 Heavy duty 8cm PWM fans

Form Factor

Form Factor 2U Rackmount Width 17.25" (438mm), Height 3.47" (88mm), 28.5" (724mm) Depth

Email: info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com