Tyrone Camarero Specifications

Camarero SDA100C3R-424

Key features

- Dual AMD EPYC™ 7003/7002 Series Processors, Socket SP3, Up to 64 Cores
- System on Chip

I

- 4TB Registered ECC DDR4 3200MHz SDRAM in 16 DIMMs
- 3 PCI-E 4.0 x16 slots, 3 PCI-E 4.0 x8 slots, M.2 Interface: 1 PCI-E 4.0 x4, M.2 Form Factor: 2280, 22110, M.2 Key: M-key
- 🖭 10 SATA3, 2 SATADOM, 4 NVMe
- Dual Gigabit LAN ports,1 dedicated IPMI LAN Port
- ASPEED AST2600 BMC graphics
- 2 USB 2.0 ports (rear), 4 USB 3.0 ports (2 rear, 2 headers)
- 8x 4-pin PWM Fans & Speed control
- 🔹 24 x 3.5" hot-swap drive bay
- 3 x 8cm hot-swap redundant PWM cooling fan(s) / 2 x 80mm rear hot-swap exhaust PWM fan(s)
- Redundant 1200W Titanium Level power supply







Processor/Cache		Front Panel	
Processor	Dual AMD EPYC™ 7003/7002 Series Processors, Socket SP3, Up to 64 Cores	LEDs	2 Network Activity LEDs, Fan Fail/System Over Heat LED, HDD activity LED, Power Status LED, Unit Identification (UID) LED
Chipset		Buttons	Power On/Off , System Reset Button
ompser		Drive Bays	
Chipset	System on Chip	HDD Bays	24x 3.5" hot-swap SAS/SATA drive bays supporting SAS3/2 or SATA3 HDDs with 12Gbps throughput
System Memory		Peripheral Bays Optional 2 x 2.5"" hot-swap drive bay,	
Memory Capacity	16 DIMM slots, Supports up to 4TB Registered ECC DDR4 3200MHz SDRAM, 8-channel memory bus For Dual CPUs: Recommended that memory be populated equally in adjacent memory banks	Optional 1 x 3.5"" internal fixed drive bay, Optional 2 x 2.5"" internal fixed drive bay	
		Power Supply	
		Redundant 1200W Titanium Level power supply	
Expansion Slot	s		
PCI-Express	3 PCI-E 4.0 x16 slots, 3 PCI-E 4.0 x8 slots, M.2 Interface: 1 PCI-E 4.0 x4, M.2 Form Factor: 2280, 22110, M.2 Key: M-key	Cooling System	
T CI LADI CIS		3 x 8cm hot-swap redundant PWM cooling fan(s) / 2 x 80mm rear hot-swap exhaust PWM fan(s)	
Integrated Onboard		Form Factor	
	indoura		
SATA	10 SATA3 (6 Gbps) ports	Form Factor	4U Rackmount
LAN	2x 1GbE LAN ports, 1 RJ45 Dedicated IPMI LAN port	Dimensions: Height : 7" (178 mm), Width : 17.2" (437 mm) , Depth : 26" (660 mm)	
Add-on Opti	ons		
Raid Card: Optical Drive:	Optional Optional	Email : info@tyronesystems.com For more/current product information, visit www.tyronesystems.com	

AMD the AMD logo inside are trademarks of Advanced Micro Devices in US and / Or other Countries

Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners