

Tyrone Camarero Specifications

Tyrone

Camarero: SDA200A3H-460

Key Feature

- AMD EPYC™ 9004 series Processors, Dual Socket SP5 supported, CPU TDP supports Up to 400W TDP
- Up to 6TB 3DS ECC RDIMM, DDR5-4800MHz in 24 DIMM slots
- Integrated IPMI 2.0 + KVM with dedicated LAN
- 32x SATA3 Hybrid via MCIO, 1 AIOM slot
- ASPEED AST2600 BMC graphics via I/O board
- 10 PCIe 5.0 x8 MCIO connectors
- 4x USB 3.0 ports (2 rear via I/O board + 2 via header)
- "60 x 2.5"/3.5" Top loading Bays (SAS/SATA) with 2 x 30 drive expander backplane
- 12 x 2.5"/3.5" Rear Bays (SAS/SATA/NVMe) with direct attached backplane"
- "2000W(80 Plus Titanium Redundant PSUs)



Processor/Cache		Drive bays	
Processor	AMD EPYC™ 9004 series Processors, Dual Socket SP5 supported, CPU TDP supports Up to 400W TDP	HDD Bays	"60 x 2.5"/3.5" Top loading Bays (SAS/SATA) with 2 x 30 drive expander backplane 12 x 2.5"/3.5" Rear Bays (SAS/SATA/NVMe) with direct attached backplane"
Chipset		Power Supply	
Chipset	System On Chip	Power Supply	2000W(80 Plus Titanium Redundant PSUs)
System Memory		Form Factor	
Memory Capacity	Up to 6TB 3DS ECC RDIMM, DDR5-4800MHz in 24 DIMM slots	Form Factor	4U Rackmount
Expansion Slot		Dimensions	
PCI-Express	1 PCIe 5.0 x16 Right Riser Slot,1 PCIe 5.0 x16 Left Riser Slot M.2 Interface: 2 PCIe 3.0 x4	Dimensions	1046.4*446.2*175.7 (D x W x H) 1191.5*446.2*175.7 (D x W x H) (with CMA)
Integrated Onboard:		<p style="text-align: center;">Email : Info@tyronesystems.com For more/current product information, Visit www.tyronesystems.com</p>	
LAN	1 Dedicated IPMI LAN port		
Add-on Options			
Raid Card	Optional		
Optical Drive	None		

• AMD the AMD logo inside are trademarks of Advanced Micro Devices in US and / Or other Countries
 • Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks . All other brands and names are the property of their respective owners