

# Tyrone Camarero Specifications

# Tyrone

## Camarero: SDI100A2N-18

### Key Feature

1U Hyper with 8 NVMe/SAS/SATA bays

Virtualization, Software-defined Storage, AI Inference and Machine Learning, Cloud Computing, Enterprise Server



- Dual Socket P+ (LGA-4189) 3rd Gen Intel® Xeon® Scalable Processors
- 32 DIMM Slots; Up to 8TB DRAM; Up to 8TB Intel® Optane™ Persistent Memory (up to 12TB with DRAM); 3200/2933/2666 ECC DDR4 LRDIMM; RDIMM; Intel® Optane™ Persistent Memory 200 series
- 3 PCIe 4.0 x16 slots with support for GPU/Accelerator cards
- Flexible networking options with 1 AIOM networking slot (OCP NIC 3.0 compatible)
- 8x 2.5" hot-swap NVMe/SATA/SAS drive bays; Optional 4x 2.5" hot-swap NVMe/SAS/SATA drive bays; 2x internal M.2 NVMe/SATA drive slots; Optional RAID support via storage add-on card
- 8 heavy duty hot-swap fans with optimal fan speed control
- 2x 1200W Redundant Titanium Level Hot-plug power supplies

<b>Processor/Cache</b>		<b>Front Panel</b>	
<b>Processor</b>	Dual Socket P+ (LGA-4189), 3rd Gen Intel® Xeon® Scalable processors, Supports up to 270W TDP CPUs (Air Cooled)	<b>LED</b>	HDD activity, LAN1 activity, Power status, System information
<b>Chipset</b>	Intel® C621A Chipset	<b>Buttons</b>	Power On/Off button, UID button
<b>System Memory</b>		<b>Drive bays</b>	
<b>Memory Capacity</b>	Slot Count: 32 DIMM slots, Max Memory (2DPC): Up to 8TB 3200MT/s ECC DDR4 Supports Intel® Optane™ persistent memory 200 series	<b>HDD Bays</b>	8 front hot-swap 2.5" NVMe*/SAS*/SATA* drive bay(s) <b>Option A:</b> Total 12 bay(s), 12 front hot-swap 2.5" NVMe*/SAS*/SATA* drive bay(s)
<b>Expansion Slot</b>		<b>Power Supply</b>	
<b>PCI-Express</b>	1 PCIe 4.0 x16 FHHL slot(s), 2 PCIe 4.0 x16 FH/10.5"L slot(s), 1 PCIe 4.0 x16 AIOM slot(s) (OCP 3.0 compatible)	<b>Power Supply</b>	2x 1200W Redundant Titanium Level Hot-plug power supplies
<b>Integrated Onboard:</b>		<b>Cooling System</b>	
<b>SATA</b>	SATA3 (6Gbps); RAID 0/1/5/10 support	8 counter-rotating 40x40x56mm Fan(s)	
<b>Network Connectivity</b>	2 RJ45 1GbE with Intel® I350-AM2 (optional), 4 RJ45 1GbE with Intel® I350-AM4 (optional), 4 SFP 1GbE with Intel® I350-AM4 (optional), 2 RJ45 10GBASE-T with Intel® X550-AT2 (optional), 2 SFP+ 10GbE with Intel® X710-BM2 (optional) 4 SFP+ 10GbE with Intel® XL710-BM1 (optional), 4 SFP+ 10GbE with Intel® X710-TM4 (optional), 2 SFP28 25GbE with Broadcom® BCM57414 (optional), 4 SFP28 25GbE (optional), 2 QSFP28 100GbE with Broadcom® BCM57508 (optional)	<b>Form Factor</b>	
<b>Add-on Options</b>		<b>Form Factor</b>	
<b>Raid Card</b>	Optional	1U Rackmount	
<b>Optical Drive</b>	None	<b>Dimensions</b>	
		<b>Dimensions</b>	
		1.7" (43 mm), Width : 17.2" (437 mm), Depth : 29.4" (747 mm)	
		<p><b>Email : <a href="mailto:Info@tyronesystems.com">Info@tyronesystems.com</a></b></p> <p><b>For more/current product information, Visit</b></p> <p><b><a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b></p>	