

# Tyrone Camarero Specifications

**Tyrone**

## Camarero SDI100C3R-14

### Key features

Web Server, Firewall Application, Data Center Optimized, Value IaaS, Cloud Computing, Compact Server, DNS & Gateway Servers, Firewall Application, CDN, Edge Nodes

- Dual sockets P+ (LGA-4189) 3rd Gen Intel® Xeon® Scalable processors
- Intel® C621A Chipset
- 16 DIMMs up to 6TB 3DS ECC DDR4-3200: LRDIMM/RDIMM/Intel® DCPMM
- 2 PCI-E 4.0 x16 FHHL; 2 PCI-E 4.0 x16 AIOM (OCP 3.0); 2 PCI-E 3.0 x2 NVMe M.2
- Dual AIOM with NCSI (OCP 3.0) for networking, 1 dedicated IPMI LAN
- 4x 3.5/2.5" hot-swap SATA/SAS drive bays
- 6 counter-rotating 4 cm PWM fans with optimal fan speed control, 2 air shrouds
- 860W redundant Platinum level 100-240Vac and 200-240 Vdc power supplies
- 1 VGA, 1 COM, 2 USB 3.0 (rear)



Processor/Cache	
Processor	Dual Socket P+ (LGA-4189), 3rd Gen Intel® Xeon® Scalable processors, Support CPU TDP 270W, Up to 40C/80T; Up to 60MB Cache CPUs with TDP higher than 185W may have support conditions due to power and thermal limitations.
Chipset	
Chipset	Intel® C621A Chipset
System Memory	
Memory Capacity	16 DIMM slots, Up to 4TB: 16x 256 GB DRAM, Up to 6TB: 8x 256 GB DRAM and 8x 512 GB PMem Memory Type: 3200/2933/2666MHz ECC DDR4 RDIMM;LRDIMM, Intel® Optane™ persistent memory 200 series
Expansion Slots	
PCI-Express	2 PCI-E 4.0 x16 FHHL; 2 PCI-E 4.0 x16 AIOM (OCP 3.0); 2 PCI-E 3.0 x2 NVMe M.2
Integrated Onboard	
SATA	SATA3 (6Gbps); RAID 0/1/5/10 support
LAN	1 Dedicated IPMI LAN port
Add-on Options	
Raid Card	Optional
Optical Drive	Optional

Front Panel	
LEDs	HDD activity LED, Network activity LEDs, Power status LED, Universal Information (UID) LED
Buttons	Power On/Off Button, UID button
Drive Bays	
HDD Bays	4x 3.5" hot-swap SATA/SAS drive bays (Default 3.5" drive trays can also support 2.5" drives.) M.2 : 2 M.2 NVMe, M-Key, 2280
Peripheral Bay	2x 2.5" drive bays (optional)
Power Supply	
	860W redundant Platinum level 100-240Vac and 200-240 Vdc power supplies
Cooling System	
	6x 4cm heavy duty fans with optimal fan speed control, 2 Air Shroud(s)
Form Factor	
Form Factor	1U Rackmount
Dimensions:	Height : 1.7" (43mm), Width : 17.2" (437mm), Depth : 25.6" (650mm)
<p><b>Email : <a href="mailto:info@tyronesystems.com">info@tyronesystems.com</a></b></p> <p><b>For more/current product information, visit</b></p> <p><b><a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b></p>	