

Tyrone Camarero Specifications

Camarero- SDI200C2R-216

Key Feature

- Virtualization, Enterprise Server, Application and data serving, Compute Intensive Applications
- Dual Socket E (LGA-4677) 5th/4th Gen Intel® Xeon® Scalable processors, supports up to 300W TDP
- 16 DIMM slots, Up to 4TB DDR5-5600MHZ/4800MHZ ECC Registered RDIMM
- 4 PCIe 5.0 x16 Low Profile (LP), 1 PCIe 5.0 x8 Low Profile (LP)
- 16 hotswap 2.5" drive bays with 8 SAS RAID (0, 1, 5, 6, 10, 50, 60) and 8 SATA drive support, 2 M.2 NVMe
- 1200W Redundant Titanium level Power Supplies
- 3x 8cm heavy duty fans with optimal fan speed control



Processor/Cache		Front Panel	
Processor	Dual Socket E (LGA-4677), 5th Gen Intel® Xeon® / 4th Gen Intel® Xeon® Scalable processors	LED	HDD activity, Network activity, Power status, System information (overheat/UID)
		Buttons	Power On/Off , system reset
System Memory		Drive bays	
Memory Capacity	16 DIMM slots, Up to 4TB DDR5-5600MHZ/4800MHZ ECC Registered RDIMM	HDD Bays	16 hotswap 2.5" drive bays with 8 SAS RAID (0, 1, 5, 6, 10, 50, 60) and 8 SATA drive support, 2 M.2 NVMe
Chipset		Power Supply	
Chipset	Intel® C741	Power Supply	1200W Redundant Titanium level Power Supplies
Expansion Slot		Cooling System	
PCI-Express	4 PCIe 5.0 x16 LP slot(s), 1 PCIe 5.0 x8 LP slot(s)	Fans	3x 8cm heavy duty fans with optimal fan speed control
Integrated Onboard:		Form Factor	
LAN	2x 1GbE port(s)	Form Factor	2U Rackmount
		Dimensions	
Raid Card	None	Dimensions	Dimensions : Height -3.5" (89mm), Width -17.2" (437mm), Depth -24.8" (630mm)
Optical Drive	Optional	<p>Email : Info@tyronesystems.com</p> <p>For more/current product information, Visit www.tyronesystems.com</p>	