

Tyrone Camarero Specifications

Camarero- SDI200C3R-28

Key features

- Virtualization, Enterprise Server, Application and data serving, Compute Intensive Applications.
- Dual Socket E (LGA-4677) 5th/4th Gen Intel® Xeon® Scalable processors, supports up to 300W TDP.
- 16 DIMM slots, Up to 4TB DDR5-4800MHz ECC Registered RDIMM.
- 4 PCIe 5.0 x16 Low Profile (LP), 2 PCIe 5.0 x8 Low Profile (LP).
- Dual ports 1G LAN/Dual ports 10G LAN
- 8 x 3.5" hot-swap SAS3/SATA drive bay.
- 3 middle 8cm Fan(s).
- 600W/650W/800W/1200W Redundant Power supply.



Processor/Cache		Front Panel	
Processor	Dual Socket E (LGA-4677) 5th/4th Gen Intel® Xeon® Scalable processors Note: supports up to 300W TDP CPUs (Aircooled) CPUs with high TDP (air cooled) only supported under specific conditions.	LED	HDD activity, Network activity, Power status, System information (overheat/UID)
Chipset	Intel® C741 Chipset	Buttons	Power On/Off button, System Reset button
System Memory		Drive bays	
Memory Capacity	Memory Capacity: 16 DIMM slots ,Up to 4TB: 16x 256 GB DRAM, Memory Type: 4800MHz ECC DDR5 RDIMM	Drive bays	8 x 3.5" hot-swap SAS3/SATA drive bay.
Expansion Slots		Peripheral bays	1x slim DVD drive bays (optional)
Integrated On-Board		Power Supply	
SATA	SATA3 (6Gbps)	Power Supply	600W/650W/800W/1200W Redundant Power supply
Network Connectivity	Dual ports 1G LAN/Dual ports 10G LAN	Cooling System	
Add-on Options		Fans	3 middle 8cm Fan(s)
Raid card	Optional	Form Factor	
Optical Drive	Optional	Form Factor	2U Rackmount
		Dimensions	
		Dimensions	Height - 3.5" (89mm), Width 17.2" (437mm) Depth 25.5" (647mm).
<p>Email : Info@tyronesystems.com</p> <p>For more/current product information, Visit www.tyronesystems.com</p>			